5. LEASE

## UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	NM-0702  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
CHARRY MOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Reid "B"
1. oil gas other	9. WELL NO.
2. NAME OF OPERATOR  Union Texas Petroleum Corporation  3. ADDRESS OF OPERATOR  P. O. Box 808, Farmington, N.M. 87499  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  AT SURFACE: 2102 ft./S; 632 ft./W lines  AT TOP PROD. INTERVAL: Same as above  AT TOTAL DEPTH: Same as above  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Change drilling procedure and APPLYSTON, N. 10 controlled in the string any proposed work. If well is including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones perting as a circulating medium. Run new 8-5/8", 24 with approx. 240 cu. ft. Class "B" cement ci	12. COUNTY OR PARISH  San Juan  14. API NO.  15. ELEVATIONS (SHOW DF, KDB, AND WD)  5726 GR  (NOTE Report results of multiple completion or zone change on Form 9-330.)  RVEY:  M.  ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*  pprox. 300 ft. using natural mud  .0#, J-55 casing to TD. Cement reculated to surface. Pressure
non-dispersed mud as the circulating medium. 15.50#, K-55 casing to TD with DV tool at ap stage with approx. 1300 cu. ft. of 65/35/6 f mix. Cement second stage with approx. 1200 to surface. Drill out the DV tool and press procedure not to change.	prox. 2150 ft. Cement first ollowed by 100 cu. ft. 50/50 Poz cu. ft. 65/35/12 Poz circulated ure test the casing. Remaining
Subsurface Safety Valve: Manu. and Type	
Signed + 12 /K Coneri	Mgr. DATE June 30, 1983
(This space for Federal or State	office use)
APPROVED BY TITLE	AS AMENORO

\*See Instructions on Reverse Side

PISTRICT ENGINEER