				rorm approve		
Form 3160-5 (November 1983)	UNITED		SUBMIT IN TRIPLICAT	Expires Augu	u No. 1004-0135 st 31, 1985	
(Formerly 9-331)	DEPARTMENT OF		/	5. LEASE DESIGNATIO		
	BUREAU OF LAN		- HEUEIVIII	SF-078926	OF TRIBE NAME	
SUN (Do not use thi	NDRY NOTICES AN s form for proposals to drill o Use "APPLICATION FOR F	D REPORTS  r to deepen or plug 'ERMIT—" for such 1	ON WELLS ROOM back to a different reservoir.			
1.			56 MAY 11 PM 1:31	7. UNIT AGREEMENT	NAME	
WELL GAS WELL	OTHER	FAI	Miliaton of contract	Gallegos (	Canyon Unit	
2. NAME OF OPERATOR		F,	ARMINGTON NEW MEXICO	8. FARM OR LEASE N		
BHP Petrol	eum (Americas)	Inc.	THE THE KILL			
3. ADDRESS OF OPERATO	) <b>g.</b>	9. WELL NO.	45			
5613 DTC P	arkway, Suite 6 Report location clearly and in	365	365			
See also space 17 be At surface	low.)					
	' FEL & 900' FS	11. SEC., T., B., M., O	W. Kutz Pictured Cliffs 11. SEC., T., E., M., OR BLE. AND			
705	TEL & 900 FS.	SURVEY OR AR				
				Sec. 25-T2	29N-R13W	
14. PERMIT NO.	15. ELEVAT	ons (Show whether D	F, RT, GR, etc.)	12. COUNTY OR PARIS	SH 13. STATE	
	539	2 ' KB	/	San Juan	NEW MEXICO	
16.	Check Appropriate I	Box To Indicate A	Nature of Notice, Report, o	r Other Data		
4.	${\mathcal V}$				DENT REPORT OF:	
TEST WATER SHUT-	OFF PULL OR ALTE	R CASING	WATER SHUT-OFF	REPAIRING	W#11	
FRACTURE TREAT	MULTIPLE CON		FRACTURE TREATMENT	ALTERING		
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING	ABANDONM		
REPAIR WELL	CHANGE PLAN	,	(Other) Well !		X	
(Other)		<u> </u>	(Note: Report resident details, and give pertinent da	ults of multiple completion in the completion report and Log in th	form.}	
The above hole to 1 with 75 s: Plug down up and termilled 6 Ran 32 jt with 204 @ 9:30 am temperaturop of Free control of the c	referenced wel 30'. Ran 3 jt. x (86 ft <sup>3</sup> ) Clas 11:00 am 04/30 sted BOPE to 75 -1/4" hole to 1 . 4½", 10.6#, J. sx (257 ft <sup>3</sup> ) 50 05/03/88. Los	1 was spud 7", 20#, s "G" cemer /88. Good 0 psi, held 385' KB & 55, R3, ST -50 Poz min t returns a	ran logs. &C csg. set @ 138 & and cement with after 30 bbl. slu t top, cement top  MAY1  CIL CC	/30/88. Drillset @ 127' KB and 1/4#/sx to surface, no 32.70' KB. Con 2% D20. Plustry displaced approx. 80	led 9-7/8" Cemented D29. ippled emented ig down i. Ran	
18. I bereby certify that	t the foregoing is true and coi	rect	, Bit			
SIGNED ZZ	Munuar Thomas		illing Foreman	DATE 05/0	04/88	
(This space for Fed	eral or State office use)					
APPROVED BY		TITLE		DATE		
COMPTENDED OF	DDD OF LY AND LASTY.					

\*See Instructions on Reverse Side