Form 3160-5 (June, 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BURGELLOG LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

	BUREAU OF LAND MANAGEMENT			Expires: March 31, 1993 /
				5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS			SF-079968	
2) Fit 19. 50 Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir.				
,	- Do not use u	IS TARRET TO PROPERTY OF FOR	PERMIT—" for such proposals	
		AIT IN TRIPLICATE	and the second second	7. If Unit or CA, Agreement Designation
		III IN IRIPLICATE		- N
L. Type of W	7 .	X Gas Well	Other	8. Well Name and No.
	Oli Well	X Gas Well	148 2002	Ropco 4-3
2. Name of		mn271/	N. N. Carlotte and	9. API Well No.
Richardson Operating Company				30-045-30394
3. Address a	nd Telephone No.		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
			lo 80203 (303) 830-8000	10. Field and Pool, or Exploratory Area
4. Location o	of Well (Footage, T	, R, M, or Survey Des	cription)	Twin Mounds PC
1830' FSL,	, 1060' FWL		*.	11. County or Parish, State
Sec. 4-T29	9N-R14W			San Juan County, NM
12.	CHECK APPRO	PRIATE BOX(s) TO	INDICATE NATURE OF NOTICE, RE	PORT, OR OTHER DATA
TYPE OF S	SUBMISSION		TYPE OF ACTION	<u> </u>
			Abandonment	Change of Plans
	Notice of Intent		Recompletion	New Construction
	_		Plugging Back	Non-Routine Fracturing
[√	Subsequent Report	.	Casing Repair	Water Shut-Off
<u></u>	_ Subsciperio Report	`	Altering Casing	Conversion to Injection
<u></u>	٠		Surface Casing/Cementing	Dispose Water
	Final Abandonment	t Notice		(Note: Report results of multiple completion on Well
			X Other: see below	
				Completion or Recompletion Report and Log form).
			all pertinent details, and give pertinent dates, includ	
If well is di	rectionally drilled, give	subsurface locations and r	measured and true vertical depths for all markets ar	nd zones pertinent to this work.)*
3/10/01	Spud 8 ≵ /4" si	urface hole. Drill to	o 137'.	
3/10/01	Drill to 137'. Ran 3 jts 7" 20# casing and set at 134.3'. Cemented with 55 sxs of Class "H" with 2% KCL.			
-,,	Circulated 3 bbis Cement to surface.			
3/12/01				
3/12/01	1000001 0000	,0,,, D,,,, to 1200		
03/13/01	TD well at 1040'. Run 25 jts 4 1/2" 10.5# casing to 1027'KB. Precede cement with			
	30 bbls water. Cemented with 45 sos of C-Lite with 2% sodium mescalite, 1/4# Cello. Tail with 80 sos Class "B" Neat			
	1/4# Cello. Release plug. Displace with 15.5 bbls water. Bumped plug 1000#, Circ 8.5 BBLS Cement. Secure Location			
	1/4# Cello. Re	elease plug. Displa	ice with 15.5 dois water. Bumped pil	ig 1000#, Circ 8.5 BBC5 Centent. Secure Location

Title: Operations Manager





Date: January 23, 2002