Form 3160-5 (June 1990) FORM APPROVED Budget Bureau No. 1004-0135 UNITED STATES Expires: March 31, 1993 2001 HOV -7 FM REPARTMENT OF THE INTERIOR 5. Lease Designation and Serial No. BUREAU OF LAND MANAGEMENT SF080247 -A 6. If Indian, Allottee or Tribe Name SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT---" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Oil X Gas Other Simmons S 1C CAT. S 2. Name of Operator 9. API Well No. D.J. Simmons Co. 30-045-30649 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 1009 Ridgeway Place. Suite 200, Farmington NM 87401 Blanco MesaVerde 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State San Juan County, NM 1050' FSI x 1940' FEL, Section 25, T29N, R9W CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION ☐ Change of Plans Abandonment Notice of Intent ☐ New Construction Recompletion Plugging Back Non-Routine Fracturing X Subsequent Report ☐ Water Shut-Off Casing Repair Conversion to Injection Altering Casing X Other Drilling Operations ☐ Dispose Water ☐ Final Abandonment Notice (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depth for all markers and zones pertinent to this work.)* 10/20/01: D. J. Simmons spudded the above well at 5:30 p.m. 10/19/01 with Aztec Rig 507. Drilled 12 ¼" hole to 286' and set 9 5/8" surface casing at 279'. Cemented surface casing with 150 sks class 'G', circ cement to surface. 10/21/01: Drilling to 2000' 10/22/01: Directional drilling to 2521. PU directional tools at 2000' for kick off point. 10/23/01: Directional drilling to 3036'. 10/24/01: Ran 7", 20 ppf intermediate casing. Cemented with 500 sks 50/50 poz + additives followed by 100 sks Class 'G' + 2% CaCl2. Circulated cement to Surface. 10/25/01: Directional drilling 6 ¼" hole to 3338' with air/mist. 14. I hereby certify that the foregoing is true and correct Date: 10/29/01 Title Operations Manager Signed Robert R. Griffee (This space for Federal or State office use) Approved by Conditions of approval, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any departmention agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

(Sundry 8-14-96 Temp Aband doc)