

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(505) 334-6178 FAX: (505) 334-6170
http://emnrd.state.nm.us/ocd/District N/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Lower	Hour, date shut-in		Length of time	shut-in	SI press. psig	Stabilized? (Yes or No)
Upper Completion	Hour, date shut-in		Length of time	shut-in	SI press psig	Stabilized? (Yes or No)
3as:			TEST SHUT-II			
2		MCI	FPD; Tested th	oru (Orifice o		
Oil:		BOPD base	ed on	Bbls. in	Hours	GravGOR
Production	rate during test	,				
		1			1	
					. >	
<u>11/9</u> 11/10	48 hours	231	10			: Lower doesn't prod
33.40	24 hours	333	10		Flowed Upper	: Lower doesn't prod
TIME (hour,date)	LAPSED TIME. PRESS SINCE* Upper Completion		PROB ZO TEMP ower Completion		E REMARKS	
Commenced at	(hour, date)*	1		Zone producing	(Upper or Lower)	
Completion	11,0,00		FLOW TE			
Lower Completion	Hour, date shut-in 11/5/99		Length of time s		SI press. Psig 10	Stabilized? (Yes or No) YES
Upper Completion	Hour, date shut-in 11/5/99		Length of time s 3 days	1	St press. Psig 428	Stabilized? (Yes or No)
		PRE-F	LOW SHUT-IN			Chabilities d'O Over en No.
Completion	Dakota		G	as	flowing	tubing
Completion	Mesaverde		G	as	flowing	tubing
Upper			<u> </u>			, , , , , , , , , , , ,
	NAME OF RESERVOIR OR POOL		TYPE OF	i i	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)
ocation of	Well:Unit Letter	N Sec 3	33_Twp_31N	Rge6	_{v_} API # 30-0_ <u>39-0</u>	7928

(Continue on reverse side)

FLOW TEST NO. 2

Commenced	d at (hour, date)	••	Zo	Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESSUR Upper Completion Lo		PROD. ZONE		REMARKS		
								
								
	te during test	based on	Bbls. ir	ıHou	rsGra	vGOR		
		MCFPL		ice or Meter):				
hereby certif	fy that the inform	nation herein conta	ined is true and co	omplete to the I	bes of my know	wledge.		
Approved	NUV I	± 1999 _{19_}	Operator_F	HILLIPS PET	ROLEUM COME	PANY		
New Mexico Oil Conservation Division			By Jun	Kenned	ly	Jim Kennedy		
Ву			Title	Well T	0			
EMPUTY OIL & GAS INSPECTOR, DISE. 43			Date					

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).