

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

November 6, 1954
(Date)

Durango, Colorado
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Blackwood & Nichols Company
(Company or Operator)

Northeast Blanco Unit
(Lease)

Floeger-Riley Drilling Company
(Contractor)

Well No. 22-36 in the SW 1/4 NE 1/4 of Sec. 36

T. 31N, R. 7W, NMPM, Blanco Inververde Pool, Rio Arriba County.

The Dates of this work were as follows: Oct 9 - 30, 1954

Notice of intention to do the work (was) ~~XXXXXX~~ submitted on Form C-102 on September 23, 1954
(Cross out incorrect words)

and approval of the proposed plan (was) ~~XXXXXX~~ obtained. Oct 9, 1954

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Spudded at 12:00 Noon on 10-9-54.

On 10-11-54, ran 7 1/2" 10-3/4" 32.75# H-40 casing - 199' set at 209'. Cemented with 200 cu Ideal Reg. cement. Cement circulated. On 10-13-54 tested 10-3/4" casing with 800 PSI for 30 minutes, before and after drilling plug & guide shoe. Hold OK.

On 10-27-54, ran 163 lbs 7" 23# & 20# J55 casing - 5044' set at 5056'. Cemented with 175 cu 4% gal mixed with 44 cu Strata-Crete followed with 75 cu Ideal Reg. cement. Temperature survey shows top of cement at 2995'. On 10-30-54 tested 7" casing with 1000 PSI for 30 minutes. Hold OK. Drilled cement & float shoe with gas. No water.

Witnessed by DeLasse Loos
(Name)

Blackwood & Nichols Co.
(Company)

Field Superintendent
(Title)

Approved: OIL CONSERVATION COMMISSION

Ernest C. ...
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name DeLasse Loos DE LASSE LOOS

Position Field Superintendent

Representing Blackwood & Nichols Company

Address P.O. Box 1237, Durango, Colorado

Oil and Gas Inspector Dist. #3.
(Title)

NOV 10 1954
(Date)

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received 3		
DISTRIBUTION		
	NO. FURNISHED	
Operator		
Santa Fe	1	
Operation Office		
State Land Office		
U. S. G. S.	1	
Transporter		
File	1	✓