In Lieu of
Form 3.50-5
(June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	FORM APPROVED
В	udget Bureau No. 1004-013
	Expires: March 31, 1993

Budget Bureau No. 1004-0135				
	March 31, 1993			

If Unit or CA, Agreement Designation

SUNDRY NOTICES	AND	REPORTS	ON	WELLS
----------------	-----	---------	----	-------

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

Lease Designation and Serial N	0.
(E-070771	

	J	7-0	10	Z		
5.	100	If Indian,	Allot	ee or	Tribe	Name

SUBMIT IN TRIPLICATE		8920005870
1. Type of Well ☐ Oil Well ☐ Gas Well ☐ □ O	Other	8. Well Name and No. ROSA UNIT #8
2. Name of Operator NORTHWEST PIPELINE CORP. c/o WILLIAMS	S PRODUCTION COMPANY	300-39-07944
3. Address and Telephone No. P. O. BOX 58500 MS 10317 SALT LAKE CITY, U		10. Field and Pool, or Exploratory Area BLANCO MESAVERDE
 Location of Well (Footage, Sec., T., R., M., or Survey Description) 1100' FSL & 900' FWL, SEC. 26, T31N, R6W 		11. County or Parish, State RIO ARRIBA COUNTY, NM
	OX(s) TO INDICATE NATURE OF NOTICE	E, REPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION		PE OF ACTION

TYPE OF SUBMISSION	TYPE OF ACTION	
□ Notice of Intent Subsequent Report □ Final Abandonment	☐ Abandonment ☐ Recompletion ☐ Plugging Back ☐ Casing Repair ☐ Altering Casing ☒ OtherTESTING	☐ Change of Plans ☐ New Construction ☐ Non-Routine Fracturing ☐ Water Shut-Off ☐ Conversion to Injection ☐ Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

06/07/94 THRU 06/09/94

MOL. ND wellhead and NU BOP. Released donut with 28,000# and TOH with 185 joints of 2-3/8" tubing. Set 5-1/2" Baker RBP at 4300'. RD BOP and tubing spool. No pressure between 5-1/2" and 7-5/8" annulus.

Install adapter flange and NU BOP. Install 5-1/2" rams. RU spear. Pulled casing to 120,000# and released casing slips. Backed off 5-1/2" casing with string shot at 3542' KB. Pulled 113 joints and a 15' cutoff. RU wireline and RIH with 7-5/8" Baker RBP. Set RBP at 3508' KB. TIH with 55 stands of 2-3/8" and circulated hole.

Pressure tested casing to 2000#. Held OK. Ran CBL from RBP at 3508' to 2000'. Top of cement at approximately 2050'. TIH and lay down remaining tubing. ND BOPs and NU wellhead. Released rig 06/09/94.

JUN 3 0 1994

 I hereby serify that the foregoing is true and correct Signed KATHY BARNEY	SR. OFFICE ASSISTANT	OIL GOM, DIV. Date 206/20/945
 (This space for Federal or State office use)		No. of the other teachers and the
Approved by	Title	Date
Conditions of approval, if any:		

*See Instruction on Reverse Side

or fraudulent statements or representations as to any matter within its jurisdiction.

JUN 2 4 1994 Jesta greces

AUULITED FOR HECOAD

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to 13. this work.)*