



(SUBMIT IN TRIPLICATE) ✓

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa FeLease No. 38 079165Unit NoneNA-01-021-397

RECEIVED

AUG 23 1956

SUNDRY NOTICES AND REPORTS ON WELLS
GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

| | |
|---|---|
| NOTICE OF INTENTION TO DRILL..... | SUBSEQUENT REPORT OF WATER SHUT-OFF..... |
| NOTICE OF INTENTION TO CHANGE PLANS..... | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | SUBSEQUENT REPORT OF ALTERING CASING..... |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | SUBSEQUENT REPORT OF ABANDONMENT..... |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | SUPPLEMENTARY WELL HISTORY..... |
| NOTICE OF INTENTION TO ABANDON WELL..... | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 15-29 is located 1600 ft. from N line and 1110 ft. from E line of sec. 29
S1/4 NE/4 29 31 5 31
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Without 11 11 11 11
(Field) (County) (Subdivision) (New Mexico Territory)

The elevation of the derrick floor above sea level is 6997.5 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to 3721', set 3705.75' of 7" CG, 200', J-35, Std. casing with guide shoe and float collar, at 3721.0', and cemented with 150 cu yd gel and 90 cu yd cement. POC 4:15 AM 7-24-56. Casing tested OK, drilled ahead.



I understand that this plan of work must receive approval in writing from the Geological Survey before operations may be commenced.

Company Pacific Northwest Pipeline Corp.Address 1034 N. BroadwayFarmington, New MexicoBy Original signed by T. A. DuganTitle District Engineer