

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>SF 078768</b>	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name <b>Rosa Unit</b>
2. Name of Operator <b>AMOCO PRODUCTION COMPANY</b>		8. Farm or Lease Name
3. Address of Operator <b>501 Airport Drive, Farmington, New Mexico 87401</b>		9. Well No. <b>54</b>
4. Location of Well UNIT LETTER <b>K</b> , <b>1585</b> FEET FROM THE <b>South</b> LINE AND <b>1575</b> FEET FROM THE <b>West</b> LINE, SECTION <b>36</b> TOWNSHIP <b>31-N</b> RANGE <b>5-W</b> NMPM.		10. Field and Pool, or Wildcat <b>Basin Dakota</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>6800' graded GL</b>		12. County <b>Rio Arriba</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input checked="" type="checkbox"/> OTHER <b>Whipstock and redrill</b> <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The 4-1/2" casing was found collapsed at 8166'. A cement retainer was set at 8081' and the Dakota was cement squeezed with 100 sacks. Amoco now proposes to set a cement plug from 5700' to 6100' over Masaverde, cut existing 4-1/2" casing at 4300', pull casing, set cement plug 4350-4200', whipstock and redrill to TD of 8475'. Request approval to whipstock hole in order to sidetrack junked hole. Approval to redrill has been obtained from U.S.G.S., Durango, Colorado. Copy of this notice is being sent to Lone Star Industries, Farmington, New Mexico, Attention: Mr. John Schalk.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Original Signed by J. ARNOLD SNELL</u>	TITLE <u>Area Engineer</u>	DATE <u>October 31, 1973</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>[Signature]</u>	DATE <u>11-1-73</u>

CONDITIONS OF APPROVAL, IF ANY: