

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 845' FNL & 790' FEL
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Commence Drlg Operations	<input checked="" type="checkbox"/>		<input type="checkbox"/>

5. LEASE SF 078999	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME San Juan 31-6 Unit	
8. FARM OR LEASE NAME San Juan 31-6 Unit	
9. WELL NO. #36	
10. FIELD OR WILDCAT NAME Basin Dakota	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 27 T31N R6W	
12. COUNTY OR PARISH Rio Arriba	13. STATE New Mexico
14. API NO. 30-039-22488	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6132' GR	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-23-80 - 12-24-80

MOL & RU. Spudded 12-1/4" surface hole at 1400 hrs. Ran 9 jts (344') of 9-5/8", 36#, K-55, ST&C & set at 358' KB. Woodco cemented w/ 275 sx C1 "B" w/ 1/4# gel flake/sx & 3% CaCl₂. Circ out 15 bbls cmt. Plud down @ 0130 hrs 12-24-80. WOC.

12-25, 26-80 Shut down for Christmas.

12-27-80 to 12-29-80 Drlg ahead to a depth of 2580'.



Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Norm H. Dyer TITLE Production Clerk DATE Dec 29, 1980

ACCEPTED FOR DEPOSIT

(This space for Federal or State office use)

APPROVED BY JAN 08 1981 TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON DISTRICT

slw **CONFIDENTIAL**

djb/