

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1660 FSL & 1520 FWL NE/SW
AT TOP PROD. INTERVAL: 1660 FSL & 1520 FWL
AT TOTAL DEPTH: 1660 FSL & 1520 FWL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Drlg Operations

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
JAN 14 1983

(NOTE: Report on well of multiple completion or zone change on Form 9-331a)

U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

RECEIVED
JAN 26 1983

OIL CON. DIV.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give surface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-28-82 to 12-29-82 Drlg ahead w/ mud
12-30-82 to 12-31-82 Ran 88 jts of 7", 20#, K-55, ST&C smls csg & set at 3730' KB. Dowell cmt'ed w/ 110 sx (241 cu.ft) of C1 "B" 65/35 poz w/ 12% gel & 75 sx (89 cu.ft) of C1 "B" w/ 2% CaCl₂. Plug displaced w/ 150 bbls & down at 1145 hrs 12-30-82. Wilson ran temp survey and found top of cmt at 2200' (Ojo Alamo at 2400'). WOC 12 hrs. Pressure tested cmt & csg to 1500# - held OK. Blew down w/ nitrogen. Drlg ahead w/ gas.
1-1-83 to 1-2-83 Drlg ahead w/ gas.
1-3-83 to 1-4-83 Reached TD of 8070' 1-3-83. Ran IES & SNP/CDL/GR Logs. Ran 200 jt of 4-1/2", 11.6# & 10.5#, K-55, USS smls & set at 8055'. FC @ 8043'. Dowell cmt'ed w/ 250 sx (543 cu.ft) of C1 "B" w/ 8% gel and 12-1/2# fine gils/sx & 0.4% retarder. Tailed w/ 100 sx (118 cu.ft) C1 "B" w/ 1/4# tuf-plug/sx & 0.4% retarder. Plug down at 0615 hrs 1-4-83. Wilson ran temp survey TOC @ 300C

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

Continued on reverse side

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE January 10, 1983
Donna J. Brace

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY

TITLE _____

DATE _____

ACCEPTED FOR RECORD

B
djb/4

*See Instructions on Reverse Side
NMOCC

JAN 24 1983

FARMINGTON DISTRICT

48A

1-3-83 to 1-4-83 cont'd

Rig released at 0830 hrs 1-4-83.

NOW WAITING ON COMPLETION.