

In Lieu of
Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use
"APPLICATION FOR PERMIT--" for such proposals

96 NOV 15 PM 1:35

SUBMIT IN TRIPLICATE

070 FERNANDO, NM

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. SF-078770
2. Name of Operator WILLIAMS PRODUCTION COMPANY	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. PO BOX 3102 MS 37-4, TULSA, OK 74101 (918) 588-4592	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 850' FSL & 850' FWL, SW SW SEC 27-34N-5W	8. Well Name and No. ROSA 112Y
	9. API Well No. 30-039-23705
	10. Field and Pool, or Exploratory Area BASIN DAKOTA/LAGUNA-SECA GAL
	11. County or Parish, State RIO ARriba COUNTY, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent <input type="checkbox"/> Subsequent Report <input checked="" type="checkbox"/> Final Abandonment	<input checked="" type="checkbox"/> Abandonment <input type="checkbox"/> Recompletion <input type="checkbox"/> Plugging Back <input type="checkbox"/> Casing Repair <input type="checkbox"/> Altering Casing <input type="checkbox"/> Other _____ <input type="checkbox"/> Change of Plans <input type="checkbox"/> New Construction <input type="checkbox"/> Non-Routine Fracturing <input type="checkbox"/> Water Shut-Off <input type="checkbox"/> Conversion to Injection <input type="checkbox"/> Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-15-96 MIRU. TIH with tbq to 3170'. CO sand and shale. Bad spot @ 2830'. Pull 10 stands.

10-16-96 TOH. TIH with bit and scraper to 3000'. TOH. TIH with cmt retainer and set @ 2950'. Unable to pump below retainer. Pull out of retainer. Broke circulation and spot 20 sx cmt plug above retainer (plug #1: 2950' - 2700'). Pull up 34 jts tbq and spot 12 sx cmt (plug #2: 1870' - 1770'). Pull 44 jts tbq and spot 12 sx cmt (plug #3: 4473' - 373'). Lay down tbq.

10-17-96 Perforate squeeze holes @ 100'. Broke circulation to surface. Pump with 90 sx cmt down 4-1/2" and out bradenhead to surface (plug #4: 100' - surface).

10-18-96 Release rig. Install dry hole marker.

RECEIVED
NOV 20 1996

OIL CON. DIST. 3

14. I hereby certify that the foregoing is true and correct

Susan Griguhn
Signed/SUSAN GRIGUHN

OFFICE ASSISTANT

Date November 11, 1996

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

APPROVED
J.S. Duane W. Spencer
NOV 19 1996
DISTRICT MANAGER

NAHCCD

ROSA #112Y
Plug and Abandonment Recap

Big A Well Service Turnkey P & A Service

Note: Mr Joe Sanchez with BLM on location during all plugging operations.

- 10-15-96 MIRU. TIH with tbg to 3170'. CO sand and shale. Bad spot at 2830'. Pull 10 stands and SDFN.
- 10-16-96 TOH. TIH with bit and scraper to 3000'. TOH. TIH with cement retainer and set at 2950'. Unable to pump below retainer. Pull out of retainer. Break circulation and spot 20 sx cmt plug above retainer (plug #1, 2950' - 2700'). Approval received from Mr. Wayne Townsend w/ BLM, 10/16/96 11:45 AM. Pull up 34 joints tbg and spot 12 sx cmt (plug #2, 1870' - 1770'). Pull 44 jts tbg and spot 12 sx cmt plug (plug #3, 473' - 373'). Lay down tbg. SDFN.
- 10-17-96 Rig up wireline truck. Perforate squeeze holes at 100'. Break circulation to surface. Pump with 90 sx cmt down 4-1/2" and out bradenhead to surface (plug #4, 100' - surface). Approval received from Mr. Wayne Townsend w/ BLM, 10/17/96 9:15 AM. Cut off wellhead and send to town. SDFN.
- 10-18-96 Rig down. Release rig. Install dry hole marker.

**ROSA #112Y
Plug and Abandonment Recap**

Big A Well Service Turnkey P & A Service

Note: Mr Joe Sanchez with BLM on location during all plugging operations.

- 10-15-96 MIRU. TIH with tbg to 3170'. CO sand and shale. Bad spot at 2830'. Pull 10 stands and SDFN.
- 10-16-96 TOH. TIH with bit and scraper to 3000'. TOH. TIH with cement retainer and set at 2950'. Unable to pump below retainer. Pull out of retainer. Break circulation and spot 20 sx cmt plug above retainer (plug #1, 2950' - 2700'). Approval received from Mr. Wayne Townsend w/ BLM. 10/16/96 11:45 AM. Pull up 34 joints tbg and spot 12 sx cmt (plug #2, 1870' - 1770'). Pull 44 jts tbg and spot 12 sx cmt plug (plug #3, 473' - 373'). Lay down tbg. SDFN.
- 10-17-96 Rig up wireline truck. Perforate squeeze holes at 100'. Break circulation to surface. Pump with 90 sx cmt down 4-1/2" and out bradenhead to surface (plug #4, 100' - surface). Approval received from Mr. Wayne Townsend w/ BLM 10/17/96 9:15 AM. Cut off wellhead and send to town. SDFN.
- 10-18-96 Rig down. Release rig. Install dry hole marker.

Rosa Unit #112Y

Final After Plugging

Dakota

Section 27, T-31-N, R-05-W, Rio Arriba County, NM

Today's Date: 10/22/86
Spud Date: 5/02/85
Completion Date: 7/14/86

17-1/2" hole

Nacimiento @ 1820'

Ojo @ 2900'

Kirtland @ 3079'

Fruitland @ 3302'

Pictured Cliffs @ 3665'

Mesa Verde @ 5800'

Gallup @ 6974'

Dakota @ 8290'

7-7/8" hole

PBTD 8500'

13-3/8" 54.5#, Cag set @ 423'

Cmt w/ 600 sx Circulated to Surface

Plug #4: 100'-Surface, Perf @ 100', Cmt w/90

Approval BLM, Wayne Townsend, 10-17-86, 9

Plug #3: 473'-373', Cmt w/12 sx

Plug #2: 1870'-1770', Cmt w/12 sx

Plug #1: 2960'-2700', Retainer Set @ 2960'.

Could not pump below perfs. Spot 20 sx plug

on top of retainer. Approval, BLM, Wayne

Townsend, 10-18-86, 11:45 AM.

Joe Sanchez, BLM, on location during all

plugging operations.

Perforations: 8290' - 8420'

4-1/2" 11.6#, N-80 Cag set @ 8546'

Cmt w 1387 cf