

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
E-505-6

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Northeast Blanco Unit

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Meridian Oil Inc. *Blackwood & Nichols*

8. Well No.

481

3. Address of Operator

PO Box 4289, Farmington, NM 87499

9. Pool name or Wildcat

Basin Fruitland Coal

4. Well Location

Unit Letter *N* : *1005* Feet From The *South* Line and *1835* Feet From The *West* Line

Section

36

Township

31B

Range

7W

NMPM

Rio Arriba

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6483' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08-24-89 Spudded well at 3:30 pm 08-24-89. Drilled to 512'. Ran 12 jts. 9 5/8", 36.0#, K-55 surface casing set at 512'. Cemented with 380 sks. Class "B" with 1/4#/sk. gel-flake and 2% calcium chloride (448 cu.ft.). Circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.

08-27-89 TD 3174'. Ran 78 jts. 7", 23.0#, K-55 casing, 3162' set @ 3174'. Cemented with 440 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride and 1/2 cu.ft./sx perlite (722 cu.ft.) followed by 100 sx Class "B" w/2% calcium chloride (118 cu.ft.). Circ to surface. WOC 12 hours. Held 1200#/30 min.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Daphne B. [Signature]

TITLE

Regulatory Affairs

DATE

8-29-89

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

Original [Signature] T. CHAVEZ

TITLE

DATE

AUG 31 1989

CONDITIONS OF APPROVAL, IF ANY: