

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

1. TYPE OF WELL GAS		5. LEASE NUMBER SF-078771	
2. OPERATOR MERIDIAN OIL INC.		6. IF INDIAN, ALL. OR TRIBE NAME	
3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499		7. UNIT AGREEMENT NAME ROSA UNIT	
4. LOCATION OF WELL 1760'N 980'E		8. FARM OR LEASE NAME ROSA UNIT	
		9. WELL NO. 217	
		10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL	
		11. SEC. T. R. M OR BLK. SEC. 11 T31N R06W NMPM	
14. PERMIT NO.	15. ELEVATIONS 6437'GL	12. COUNTY RIO ARRIBA	13. STATE NM
16. NOTICE OF INTENTION TO: Change Plans			
17. Describe proposed or completed operations			

Attached is a revised operations plan, BOPE diagram and anticipated production facilities diagram on the subject well.

RECEIVED
APR 03 1990
OIL CON. DIV.
DIST. 3

18. AUTHORIZED BY:

REGULATORY AFFAIRS

919189
DATE

NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.

=====
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITION OF APPROVAL, IF ANY:

DATE

Ken Townsend

RECEIVED

NOV 10 1964
U.S. AIR FORCE

Well Name: 217 ROSA UNIT 1760'N 980'E
 Sec. 11 T31N R06W RIO ARRIBA NEW MEXICO
 BASIN FRUITLAND COAL Elevation 6437'GL

Formation tops: Surface- SAN JOSE

Ojo Alamo- 2510
 Kirtland- 2620
 Fruitland- 3043
 Fruitland Coal Top- 3128
 Fruitland Coal Base- 3275
 Intermediate TD- 3108
 Total Depth- 3215
 Pictured Cliffs- 3277

Logging Program: Mud logs from intermediate to total depth.

Mud Program:	Interval	Type	Weight	Visc.	F1. Loss
	0 - 200	Spud	8.4 - 8.9	40-50	no control
	200 - 3108	Non-dispersed	8.4 - 9.1	30-60	no control
	3108 - 3215	Formation Water	8.4		no control

Casing Program:	Hole Size	Depth	Interval	Csg. Size	Weight	Grade
	12 1/4"	0 - 200		9 5/8"	32.3#	H-40
	8 3/4"	0 - 3108		7"	20.0#	K-55
	6 1/4"	3058 - 3215		5 1/2"	15.5#	K-55
Tubing Program:		0 - 3215		2 7/8"	6.5#	J-55

Float Equipment: 9 5/8" surface casing - saw tooth guide shoe.

7" intermediate casing - guide shoe and self-fill insert float valve. Three centralizers run every other joint above shoe. Run insert float one joint above the guide shoe.

5 1/2" production casing - float shoe on bottom and a pre-drilled liner run to the 7" casing with a minimum 50' overlap. Liner hanger is a double slip grip type.

Wellhead Equipment: 9 5/8" x 7" x 2 7/8" x 11" 3000 psi xmas tree assembly.

Cementing:

9 5/8" surface casing - cement with 106 sacks of class "B" cement with 1/4# floccule/sack and 3% calcium chloride (125 cu ft. of slurry, 100% excess to circulate to surface). WOC 12 hours. Test casing to 600 psi for 30 minutes.

7" intermediate casing - lead with 32 sacks of 65/35 class "B" poz with 6% gel, 2% calcium chloride and 1/2 cu ft. Perlite/sack (10.3 gallons of water/sack) tail with 100 sacks of class "B" with 2% calcium chloride. 180 cu ft. of slurry, 100% excess to cover the Ojo Alamo. Run temperature survey at 8 hours. WOC 12 hours. Test casing to 1500 psi for 30 minutes.

5 1/2" liner - do not cement.

BOP and Tests:

Surface to intermediate TD - 11" 2000 psi(minimum) double gate BOP stack (Reference Figure #1). Prior to drilling out surface casing, test rams to 600 psi for 30 minutes.

Intermediate TD to TD - 7 1/16" 2000 psi(minimum) double gate BOP stack (Reference Figure #2). Prior to drilling out intermediate casing, test rams to 1500 psi(minimum) for 30 minutes.

From surface to TD - choke manifold (Reference Figure #3).


Pipe rams will be actuated at least once each day and blind rams actuated once each trip to test proper functioning. A Kelly cock valve and drill string safety valves to fit each drill string will be maintained and available on the rig floor.

Addition Information:

The Fruitland coal formation will be completed.
This gas is dedicated.
The E/2 of Section 11 is dedicated to this well.

TOP SET FRUITLAND COAL


FIGURE #1



Minimum BOPE installation for a typical Fruitland Coal well from surface to intermediate TD. 11\"/>

TOP SET FRUITLAND COAL


FIGURE #2



Minimum choke manifold configuration for a typical Fruitland Coal well from surface to TD. 2\"/>

TOP SET FRUITLAND COAL


FIGURE #2



Minimum BOPE installation for a typical Fruitland Coal well from intermediate TD to TD. 6\"/>

TOP SET FRUITLAND
COAL WELL BOPE.

UPDATED
9/8/89



MERIDIAN OIL

ANTICIPATED
PRODUCTION FACILITIES
FOR A
FRUITLAND WELL

J. Falconi

4/28/89