Ferm 3160-5 (November 1983) (Formerly 9-331)

16.

UNITED STATES SUBMIT IN TRIPLICATE Other instructions on re DEPARTMENT OF THE INTERIOR verse side)

BUREAU OF LAND MANAGEMENT

Budget Bureau No. 1004-0135 Expires August 31, 1985

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

5. LEASE DESIGNATION AND SERIAL NO

SF-078995

SUNDRY NOTICES AND REPORTS ON WELLS

	Use "APPLICATION FOR PERMIT—" for such proposals.)	
ī.	OIL GAS GO JAN 12 AM 11: 19 WELL WELL WOLLES	7. UNIT AGREEMENT NAME
ÿ	NAME OF OPERATOR	San Juan 31-6 Unit 8. FARM OR LEASE NAME
	Northwest Pipeline Corporation	San Juan 31-6 Unit
3.	ADDRESS OF OPERATOR	9. WELL NO.
	3539 East 30th Street - Farmington, NM 87401	#225
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1535' FSL & 1610' FWL NE/4 SW/4	Basin Fruitland Coal 11. SBC., T., E., M., OR BLK. AND SURVEY OF AREA Sec. 31K, T31N, R6W
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISE 13. STATE
	6207' GR	Rio Arriba New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF REPAIRING WELL
PRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING
SHOOT OR ACIDIZE FARBOT 1990 SHOOTING OR ACIDIZING ABANDONMENT®
REPAIR WELL (Other) Drilling Operations
(Other) OIL CON. DIV. 1 (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATO STEIN state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally writed, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11-2-89: MOL & RU. Drilled MH and RH. Spudded well at 2015 hrs 11/2/89.

11-3-89: Ran 5 jts (218') 9-5/8", 32.3#, K-55, ST&C Lonestar ERW casing. Set at 234' KB. Cemented w/ 124 sx (148 cu.ft.) C1 "B" w/ 3% CaCl₂ and 1/4# gel flake/sk. Displaced w/ 16 bbls water. Did not circulate cement. WOC 1 hr. Ran in backside w/ 1" pipe. Circulated cement and water spacer. Pumped 50 sx cement. Circulated 5 bbls cement. complete at 1015 hrs. 11/3/89. WOC 12 hrs. Pressure tested 9-5/8" casing to 600#, held ok.

11-4-89: Drilling w/ Benex.

11-5-89: Drilling w/ Benex. TD'd well w/ mud. Conditioned hole for casing & TOH LDDP and DCs.

Ran 68 jts (2904') 7", 23#, K-55, LT&C, CF&I smls casing. Set at 2917' KB. 11-6-89: FC at 2873' KB. Cemented w/ 330 sx (683 cu.ft.) C1 "B" 65/35 poz w/ 12% gel and 1/4# cele-flake/sk. Tailed w/ 75 sx Cl "B" w/ 1/4# cele-flake/sk. Displaced w/ 113 bbls water. Circulated 13 bbls cement. Plug down at 0900 hrs 11/6/89. Rig released at 1400 hrs 11/6/89.

18. I hereby certify that the foregoing is true and correct SIGNED Carrie Harmon	TITLE Production Assistant	DATE _/-5-90
(This space for Federal or State office use) APPROVED BY	TITLE	ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:		FFD A.S

NMOCD

*See Instructions on Reverse Side

FEB 02 1990 FARMINGTON RI