State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised 1-1-89

P.O. Box 1980, Hobbs, NM 88240 P.O. B x 2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease STATE STATE FEE DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Office GAS Lease No. E-346-25 7. Lease Name or Unit Agreement Name San Juan 31-6 Unit San Juan 31-6 Unit Reserved	District Office				
SUNDRY DO, Artest, NM \$210 STATE FEE	DISTRICT I P.O. Box 1980, Hobbs, NM 88240	-		WELL API NO. 30-039-24638	
S. Sato Old & But Leave No. 18-346-2-5	• * •			5. Indicate Type of Lease	
(DO NOT USE THIS FORM FOR PROPOSAL STO DRILL OR TO DEEPEN OR PLUB BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMAT" (FORM C-101) FOR SUCH PROPOSALS) 1. Type of Wall. 2. Name of Operator Wall. 2. Ones Such PROPOSALS) Phillips Petroleum Company Phillips Petroleum Company Phillips Petroleum Company San Juan 31-6 Unit 8. Wall Na 223 Phillips Petroleum Company 300 West Arrington, Suite 200, Farmington, N.M. 87401 8. Wall Na 223 9. Pool series or Wilder Basin Fruitland Coal 4. Wall Consider Liak Letter L: 1956 Peel Front The South Lios and 1162 Peel Front The West Lise Socies 32 Towards) 31N Range 6W NMPM Rio Arriba County 10. Bereilon (Show whether DF, RKE, RT, CR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. 6-20-90 - RU Cassing Crew. Ran 7", 23F, J-55, ST&C Cassing set at 2953'. Cemented with 500 SX 65/35 PDZ with 12% gel s 1/4# celloflake/sk. Circ. 200SX Cement. Plug down at 12:45A. Bumped plug with 1500 psi - okay. NO BOP, Set casing slips W/55,000% RD & Released RB and Wireline ran GR/CCL from 3120' to 2840'. Perf. with 4JSFF (.75" dia.) 2962'-3116' (Total 312 holes). RU cudd to run 2 7/8", 6.5#, J-55 tubing set at 3029.20' ND Cudd. Rig down & released rig. PANY August 1, 1990 AUG 2 1990 OIL CON. DIV DOMANDA A. J. Kieke, Jr. Area Landman TREMPORTINAM A. J. Kieke, Jr. Area Landman TREMPORT NAME A. J. Kieke, Jr. Area Landman TREMPORT NAME A. J. Kieke, Jr. Area Landman TREMPORT NAME A. J. Kieke, Jr. Area Landman				6. State Oil & Gas Lease No.	
Name of Operator	(DO NOT USE THIS FORM FOR PRODIFFERENT RESE	OPOSALS TO DRILL OR TO DEEPEN I RVOIR. USE "APPLICATION FOR PER	OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name	
E Name of Operator Phillips Petroleum Company Phillips Petroleum Company Phillips Petroleum Company I. Address of Operator 300 West Arrington, Suite 200, Farmington, N.M. 87401 I. Well Loads Unit Letter L : 1956 Peet From The South Line and 1162 Feet From The West Line Section 32 Township 31N Range 6W NMTM Rio Arriba County II. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: ERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON PLUG AND ABANDON PLUG AND ABANDON PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDON PLUG AND ABANDONMENT COMPRET. COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT SEE RULE 1103. 6-20-90 - RU Casing Crew. Ran 7", 23#, J-55, ST&C Casing set at 2953'. Cemented with 500 SX 65/35 POZ with 12% gel & 1/44 celloflake/sk. Circ. 2005K Cement. Plug down at 12:45A. Bumped plug with 1500 psi - okay. ND BOP, Set casing slips W/55,000# RD & Released Rig at 4:00 A.M. 7-12-90 - Basin Wireline ran GR/CCL from 3120' to 2840'. Perf. with 4JSPF (.75" dia.) 2962'-3116' (Total 312 holes). RU Cudd to run 2 7/8", 6.5#, J-55 tubing set at 3029.20' ND Cudd. Rig down & released rig. I booty certly that the information above is true and complete to the best of my knowledge and belief. DIST. 3 MAUG 2 1990 TIME PLUG ON THE PLUG ON	OR GAS	OTHER		San Juan 31-6 Unit	
A Address of Operator 300 West Arrington, Suite 200, Farmington, N.M. 87401 Basin Fruitland Coal (Well Lostice Unit Letter L : 1956 Feet From The South Line and 1162 Feet From The West Line Socion 32 Township 31N Runge 6W NMFM Rio Arriba County 10. Elevation (Show whether DY, REE, RT, GR, etc.) The Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON PLUG AND ABANDON COMMENCE DRILLING OPNS. PLUG AND ABANDON PLUG AND ABANDON COMMENCE DRILLING OPNS. PLUG AND ABANDON COMMENT JOB COMM	2. Name of Operator			8. Well No. 223	
Util Letter L ; 1956 Peet From The South Line and 1162 Peet From The West Line	3. Address of Operator				
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK	t. Well Location				
NOTICE OF INTENTION TO: ERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB THER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent data), and give pertinent data; including estimated data of starting any proposed word). SEE RULB 1103. 6-20-90 - RU Casing Crew. Ran 7", 23#, J-55, ST&C Casing set at 2953'. Cemented with 500 SX 65/35 POZ with 12% gel & 1/4# celloflake/sk. Circ. 200SX Cement. Plug down at 12:45A. Bumped plug with 1500 psi - okay. ND BOP, Set casing slips W/55,000# RD & Released Rig at 4:00 A.M. 7-12-90 - Big "A" #22 Ran 5 1/2", 23#, Pl10 liner set at 2846.80'. 7-13-90 - Basin Wireline ran GR/CCL from 3120' to 2840'. Perf. with 4JSPF (.75" dia.) 2962'-3116' (Total 312 holes). RU Cudd to run 2 7/8", 6.5#, J-55 tubing set at 3029.20' ND Cudd. Rig down & released rig. PLUG AND ABANDONMENT ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT COMMENT COMMENT OF START AND CEMENT AND ABANDONMENT COMMENT OPNS. PLUG AND ABANDON	Section 32			NMPM Rio Arriba County	
EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB THER: CASING TEST AND CEMENT JOB	• • •	* * *			
CASING TEST AND CEMENT JOB OTHER: OT	ERFORM REMEDIAL WORK	PLUG AND ABANDON			
THER: OTHER: OTHER:					
12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed worth) SEE RULE 1103. 6-20-90 - RU Casing Crew. Ran 7", 23#, J-55, ST&C Casing set at 2953'. Cemented with 500 SX 65/35 POZ with 12% gel & 1/4# celloflake/sk. Circ. 200SX Cement. Plug down at 12:45A. Bumped plug with 1500 psi - okay. ND BOP, Set casing slips W/55,000# RD & Released Rig at 4:00 A.M. 7-12-90 - Big "A" #22 Ran 5 1/2", 23#, Pl10 liner set at 2846.80'. 7-13-90 - Basin Wireline ran GR/CCL from 3120' to 2840'. Perf. with 4JSPF (.75" dia.) 2962'-3116' (Total 312 holes). RU Cudd to run 2 7/8", 6.5#, J-55 tubing set at 3029.20' ND Cudd. Rig down & released rig. PLEE IVE AUG 2 1990 I hereby certify that the information above is true and complete to the best of my knowledge and bedief. DIST. 3 DATE August 1, 1990 (505) TILEPHONE NO. 599-3410 (Dists space for State Use)	OTUES.				
6-20-90 - RU Casing Crew. Ran 7", 23#, J-55, ST&C Casing set at 2953'. Cemented with 500 SX 65/35 POZ with 12% gel & 1/4# celloflake/sk. Circ. 200SX Cement. Plug down at 12:45A. Bumped plug with 1500 psi - okay. ND BOP, Set casing slips W/55,000# RD & Released Rig at 4:00 A.M. 7-12-90 - Big "A" #22 Ran 5 1/2", 23#, Pl10 liner set at 2846.80'. 7-13-90 - Basin Wireline ran GR/CCL from 3120' to 2840'. Perf. with 4JSPF (.75" dia.) 2962'- 3116' (Total 312 holes). RU Cudd to run 2 7/8", 6.5#, J-55 tubing set at 3029.20' ND Cudd. Rig down & released rig. REFERENCE OF State Use) August 1, 1990 (505) THLEPHONE NO. 599-3410			<u> </u>		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE SIGNATURE A. J. Kieke, Jr. Area Landman TELEPHONE NO. 599-3410 (This space for State Use)	6-20-90 - RU Casing Cr 65/35 POZ wi Bumped plug Rig at 4:00 / 7-12-90 - Big "A" #22 / 7-13-90 - Basin Wireling 3116' (Total	th 12% gel & 1/4# cellowith 1500 psi - okay. Note A.M. Ran 5 1/2", 23#, Pll0 1 ne ran GR/CCL from 3120 312 holes). RU Cudd to	flake/sk. Circ. D BOP, Set casi iner set at 284 ' to 2840'. Pe o run 2 7/8", 6	200SX Cement. Plug down at 12:45A. ing slips W/55,000# RD & Released 46.80'. erf. with 4JSPF (.75" dia.) 2962'- 5.5#, J-55 tubing set at 3029.20'	
(This space for State Use)	SIGNATURE SIGNATURE	<u>/ </u>	belief. OIL CO	N. DIV T. 3 August 1, 1990 (505)	
			Millen	MID 0 0 1000	

CONDITIONS OF AFFROVAL, IF ANY: