

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SECRET BY AUTHORITY  
(Other instructions on reverse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. SF-078999	
2. NAME OF OPERATOR Phillips Petroleum Co.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 300 W. Arrington, Suite 200, Farmington, NM 87401		7. UNIT AGREEMENT NAME San Juan 31-6 Unit	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit K, 1839' FSL & 1734' FWL		8. FARM OR LEASE NAME	
14. PERMIT NO. 30-039-24672		9. WELL NO. 219	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6470'		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34, T31N, R6W	
		12. COUNTY OR PARISH Rio Arriba	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other) Spud & Drilling

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-9-90

MIRU Aztec Well Service Rig #289.  
Spudded 12-1/4" hole @ 12:30 P.M.  
Ran 9-5/8", 36#, K-55, ST&C Casing Set @ 282'  
Cemented w/250 sx C1 "G" Cement w/3% CaCl2 & 1/4# gelflake per sk. (Dowell)  
Circulated 90 sx cement.  
Plug down @ 1:00 A.M.  
WOC

RECEIVED  
JUN 29 1990  
OIL CON. DIV.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

*L.M. Sanders*  
L.M. Sanders

TITLE Supv. Regulatory Affairs

DATE 6-14-90

(This space for Federal or State office use)

APPROVED BY

TITLE

ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

JUN 27 1990

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY