

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.	30-039-24937
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. Subsurface Gas Lease No.	347-39
7. Lease Name or Unit Agreement Name	San Juan 31-6 Unit 009259
8. Well No.	SJ 31-6 Unit #214
9. Pool name or Wildcat	Basin Fruitland Coal 71629

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	017654
2. Name of Operator Phillips Petroleum Company	
3. Address of Operator 5525 Highway 64, NBU 3004, Farmington NM 87401	
4. Well Location Unit Letter <u>G</u> : <u>1560'</u> Feet From The <u>North</u> Line and <u>981</u> Feet From The <u>East</u> Line Section <u>36</u> Township <u>31N</u> Range <u>6W</u> NMPM Rio Arriba County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Install PC Pump ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A progressive cavity pump (stator and rotor) has been installed on the subject well. Details are as follows:

Progressive Cavity Pump (stator) set @ 3279'

2-7/8" tubing set @ 3310' (185 jts total)

"F" nipple set @ 3278'

Rotor set with 131 .875" rods, 1.125" X 20' polish rods. Rotor set down in stator @ 3279'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Patsy Clugstson TITLE Regulatory Assistant DATE 9-24-98

TYPE OR PRINT NAME Patsy Clugstson TELEPHONE NO. 505-599-3454

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERRIN

DEPUTY OIL & GAS INSPECTOR, DIST. #3

APPROVED BY _____

TITLE _____ DATE SEP 28 1998

CONDITIONS OF APPROVAL, IF ANY: