
Form 3160-5 (June 1990)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

FORM APPROVED

	ATD A 4 A 5 4 A 5 5 A 5 A 5 A 5 A 5 A 5 A 5	Expires: March 31, 1993
BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals  SUBMIT IN TRIPLICATE		5. Lesse Designation and Serial No.
		SF-078995
		6. If Indian, Allottee or Tribe Name
		$\int \mathbb{R}^{n} dx  g_{R}$
		7. If Unit or CA, Agreement Designation
1. Type of Well		San Juan 31-6 Unit
Oil   X Gas   Other   Other		8. Well Name and No.
2. Name of Operator	229	
Phillips Petroleum Company	9. API Well No.	
3. Address and Telephone No.	(505) 599-3412	
300 W. Arrington, Suite 200, Farmington, NM 87401		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Basin Fruitland Coal
Unit L , 1810' FSL & 1111' FWL		11. County or Parish, State
Sec. 28 , T <sub>31</sub> N, R 6 W		Rio Arriba, NM
12. CHECK APPROPRIATE BOX(s) 1	O INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other	_ Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state all pert	inent details, and give pertinent dates, including estimated date of starting	any proposed work. If well is directionally drilled,
give subsurface locations and measured and true vertical de	pths for all markers and zones pertinent to this work.)*	
10.00.00		
10-30-90	201 0 11 1 10 1//11 1 2 2 2 2 2	134 B 0 5 (0)
MIRU Aztec Well Service Rig No.	301. Spudded 12-1/4" hole @ 11:00	AM. Ran 9-5/8",

36#, K-55, ST&C casing set @ 287.68'. RU Halliburton and cemented w/250 Sx Class B cement w/3% CaCl2 and 1/4# Flocele/Sk. Circ. 90 Sx cement. Plugged down @ 7:00 PM. Bumped plug with 800 psi. WOC 12 hours. NU BOP and pressure tested to 1000 psi - okay.



ACCEPTED FOR RECORD

14. I sereby certify that the foregoing is true and corned  Suppose Signed Destrain for R. Q. Willed	Title	Drilling Supervisor NOV 15 1990	
(This space for Federal or State office use)  Approved by Conditions of approval, if any:	Tide	FARMINGTON RESOURCE AREA BY	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.