

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
Min. Agmt. #701-90-0002

6. Indian, Allottee or Tribe Name
Jicarilla Apache Tribe
N.M.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Robert L. Bayless

3. Address and Telephone No.

PO Box 168, Farmington, NM 87499 (505) 326-2659

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1500' FSL & 790' FWL
Section 17, T31N, R3W

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jicarilla 31-3-17-1

9. API Well No.

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Reached TD of 3809' on 8/14/91. Circulate and trip out. Rig up Halliburton Logging Service and run logs. Trip in hole open ended. Circulate. Wait on cementers. Rig up Halliburton. Plugged well as follows:

Plug #1 - 260 sx. Class B neat (307 cf) set from 3724' to 3015'. Pull 25 stands (2159'). Circulate for 4 hours. Trip in hole and tag plug #1 @ 3015'. Lay down drill pipe. Set Plug #2 (surface) from 219' to surface using 80 sx. (94 cf) Class B cement. Lay down remaining drill pipe. Final plug down at 2:15 a.m. 8/16/91.

Plug and abandon. Jet pits and rig down. Rig released at 4:30 a.m. 8/16/91.

RECEIVED

SEP 12 1991

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Engineer Date 8/16/91

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side