

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-25189
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name
Quinlan Ranch Q2

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	8. Well No. 2
2. Name of Operator DEKA Exploration, Inc.	9. Pool name or Wildcat Wildcat - Entrada
3. Address of Operator P.O. Box 14057, Oklahoma City, OK 73113	
4. Well Location Unit Letter <u>H</u> : <u>3100</u> Feet From The <u>South</u> Line and <u>330</u> Feet From The <u>East</u> Line Section <u>1</u> Township <u>31N</u> Range <u>2E</u> NMPM <u>Rio Arriba</u> County	

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
8431' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/26/92 Up Date:

Perforated Morrison from 2410'-2418'. Set cast iron bridge plug @ 2400'. Perf. Burrow Canyon from 2120'-2130'. Set cast iron bridge plug @ 2100'. Perf. L. Dakota 1984'-1988'. Set cast iron bridge plug @ 1974'. Perf. Niabrara from 1198'-1270' OA. Broke down with 1500 gals treated Diesel and fraced with 86,798 gals 70 Quality Foamed Diesel and 75,000# 20/40 Arizona sand; perf. Niabrara from 938'-1030'. Broke down with 1750 gals teated Diesel and fraced with 92,922 gals 70 Quality Foamed Diesel and 76,700# 20/40 Arizona sand. Well is flowing back at this time.

RECEIVED
SEP 30 1992

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jamew L. Nondorf TITLE President DIST. 3 DATE 8/31/92
TYPE OR PRINT NAME Jamew L. Nondorf (405) 749-0004 TELEPHONE NO.

(This space for State Use)

APPROVED BY Original Signed by FRANK J. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE SEP 30 1992
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

SEP 28 1992

OCD, HOBBS OFFICE