Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR RUREAU OF LAND MANAGEMENT

\cap		FOR	a mu	PPR	OVE	•
٠.	_	FOI Budget B	uresu	No.	1004	-0135
31	í	Expire	s: M	arch	31, 19	93

<u>.</u>	Ĺ	77	Expires.	MAICH	21,	1773	
			Designat				0.

BUREAU OF	LAND MANAGEMENT	5. Lease Designation and Serial No.			
SUNDRY NOTICES Do not use this form for proposals to describe the second secon	2 STC+078995 6. If Indian, Allogical or Tribe Name				
USO ALLEGATION TO	THE CHIMIT — TOT SUCH Proposals				
SUBMIT	7. If Unit of CA. Agreement Designation San Juan 31-6 Unit				
I. Type of Well Oil SS Well Other	8. Well Name and No.				
2. Name of Operator		39E			
Phillips Petroleum Company	•	9. API Well No.			
3. Address and Telephone No.		30-039-25294			
5525 Hwy. 64, NBU 3004, Farming A. Location of Well (Footage, Sec., T., R., M., or Survey D.		10. Field and Pool, or Exploratory Area Basin Dakota			
Unit P, 798' FSL & 1184' FEL		11. County or Parish, State			
Section 28, T-31-N, R-6-W					
	Rio Arriba, N.M.				
12. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPOR	IT, OR OTHER DATA			
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	Abandonment	Change of Plans			
	Recompletion	New Construction			
Subsequent Report	Plugging Back	Non-Routine Fracturing			
—	Casing Repair	Water Shut-Off			
Final Abandonment Notice	Altering Casing XXX Other As Per NTL-FRA-90-1	Conversion to Injection			
	Cother	Dispose Water [Note: Report results of multiple completion on Well			
		Completion or Recompletion Report and Log form.)			
give subsurface locations and measured and true vertices	Il pertinent details, and give pertinent dates, including estimated date of starting cal depths for all markers and zones pertinent to this work.)*	any proposed work. If went is directionally distinct,			
Despription of cement job to f	ulfill requirements for protection of	usable water zones			
including the Ojo Alamo Format					
	arted: 2200 Time Completed: 24	00 hrs			
Hole Size 8-3/4" Casing	Size 7",23# K-55 New; Casing Se				
Turbo Centralizers at 3789,	3711 , <u>3628</u> , <u>3542</u> , <u>2482</u> , <u>2</u>	2438 , 2495 , 2349			
Spring Type Centralizers		·			
Mud Flush Bbls, Spacer 20 Fresh Water.					
Stage 1:	/100/ 7 1 1 1 // 1 11 1 1/ 1 0 10				
Lead Slurry 600 sxs 65:35 POZ w/12% gel + 1/4 /xk cello-seal Mixed @ 12.					
Mid Slurry Tail Slurry 150 and Cl. B x/2% C	12C1 + 1/1/ck collocal mixed (15 6 pr				
Tail Slurry 150 sxs Cl B w/2% CaCl + 1/4 // sk celloseal mixed @ 15.6 ppg					
Stage 2: Lead Slurry					
Mid Slurry					
Tail Slurry					
Volume Cement Circulated 10 Bbls/Sacks Displaced Plug with 149.5 Bbls/Resh Water.					
Average ressure rsi, Average Rate brn, bumped ring with rsi.					
14. I hereby certify that the foregoing is true and correct					
Signed L. E. Kolinson I. E. Robin	nson Tide Sr. D&P Engineering	Date1-20-94			
(This space for Federal or State office use)					
Approved by	ACCEP1	ED FÖR RECORD			

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United Angles Ingliang Gatious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

**See Instruction on Reverse Side

**EADMINICTON DISTRICT

FARMINGTON DISTRICT OFFICE

Ð٧