

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
WILLIAMS PRODUCTION COMPANY

3. Address and Telephone No.
PO BOX 3102 MS 37-4, TULSA, OK 74101 (918) 588-4592

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
640' FSL & 950' FWL, SW/4 SW 1/4 SEC 22-31N-5W

5. Lease Designation and Serial No.
SF-078770

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation
ROSA UNIT

8. Well Name and No.
ROSA UNIT #132

9. API Well No.
30-039-25314

10. Field and Pool, or Exploratory Area
BLANCO MV

County or Parish, State
RIO ARRIBA, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

TYPE OF ACTION

- ☐ Abandonment
☒ Recompletion
☐ Plugging Back DAKOTA
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-29-1998 MOL & RU. Receive tbg. & tally. Bleed #900 pressure. ND WH & NU BOP. RU Blue Jet. Try to log @ 2400' - slow going. Work logging tool to 4500' & pull out. Had heavy mud & paraffin cement. Release Blue Jet. RIH w/ tbg. Circulate clean from 2500', 3500', 4000', 4700' & 5500'. Pull up 3 stands & circulate hole clean. SDON.

4-30-1998 TIH w/ tbg. to 6500', break circulation & clean out hole. TIH to 7141' & circulate - still colored water. TOH w/ tbg. & bit. RU Blue Jet & run GSL & CBL from 4200' - 6300'. TOC above 4200'. Good cmt 5110' and up. found cement above 4500'. RU to pressure test casing. Pressure test to #3300 - held OK for 15 min. RIH w/ tbg. (45 stands). SD strong winds & lightning. Secure location & SDON.

5-01-1998 TIH & set bottom of tbg @ 6078'. Circulate hole clean - no debris, some color. Secure location. Install valve on tbg. & shut well in. Ready to spot acid & frac on Monday (5/4/98).

CONTINUED ON PAGE 2

14. I hereby certify that the foregoing is true and correct

Signed

Susan Griguch
SUSAN GRIGUCH

Title CLERK

Date May 18, 1998

(This space for Federal or State office use)

Approved by

Title

Date

AUG 24 1998

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fraudulent statements or representations as to any matter within its jurisdiction.

OPERATOR

5-06-1998 Well had died early in the morning. TIH opened with 2-3/8" tubing to 3300'. Started compressor and unloaded well. Well making a lot of water but no sand. TIH to 4540' and unload well with compressor. Water rate slowed down with a trace of sand. TIH and tag sand at 5680'. Only 3 perfs were covered with sand. Cleaned out and ran 3 soap sweeps. POH to 5200'. Turn over to night watch.

5-07-1998 Tagged 40' of fill @ 5700'. Clean to BP @ 5740'. PU to 5240'. Ran sweeps. RIH and tagged sand @ 5725'. Secure location for the night.

5-08-1998 SICP = 800#. Blew well down. took pitot gauge through 1" at 390 MCFD. TIH and tagged CIBP - no fill. TOH. TIH with 6-3/4" bit. Picked up swivel and drilled CIBP. Let head blow off and pushed the remainder of the CIBP to 5852'. Ran soap sweeps. Well making water and sand. POH to 5200' and ran two soap sweeps. Turn over to night watch.

5-09-1998 TIH with 6-1/8" bit and tag up at 5850'. Push CIBP to 6050'. Clean up well with soap sweeps. Well quit making sand. Push CIBP to 6115'. Run soap sweeps and POH to 5200'. Turn over to night watch.

5-10-1998 TIH with 6-1/8" bit and tag fill at 6095'. Clean out to CIBP and push to 6220'. Clean well with soap sweeps every hour. Well is making a trace of sand and a little water. TOH. Pitot gauge well at 1357 MCFD. TIH to 6220' and run one soap sweep. POH and land tubing at 6009' KB. Ran notched collar, one jt. SN, and 193 jts of 2-3/8", 4.7#, J-55, EUE tubing (5996.54'). ND BOP and NU wellhead. Rig down. SI well.