

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (505) 334-8178 FAX: (505) 334-8170

(505) 334-8178 FAX: (505) 334-8170 http://emnrd.state.nm.us/ood/District IM/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

	1 / NOI	RTHWEST N	EW MEXICO	PACKER	R-LEAKAGE TEST					
Operator	Villia.	ms Proc	Lease Nan	10 K 05	50 Unix	Well No_ <u>184</u>				
Location of V	Vell:Unit Letter_	ှိ _{Sec_2}	. <u>2</u> Twp <u>3/</u> 3	ر Rge <u>ہ کر د</u>	⊭API#30-0 <u>39</u> z	543600				
	NAME OF RESER		PROD. r Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)					
Upper Completion	PC		69.	5	flow	769				
Lower Completion	my		693		Llow	The				
PRE-FLOW SHUT-IN PRESSURE DATA										
Upper Completion	Hour, date shut-in	0 -	Length of time	shut-in	SI press. Palg 574	Stabilized? (Yes or No)				
Lower Completion	Hour, date shut-in	8-13-01	1726	15	SI press. Psig	Stabilized? (Yes or No)				
		2-11-		r	Olansia (194)	K D				
				·						
(hour,date)	SINCE"	Upper Completion	Lower Completion	TEMP.						
1040 8-17	246-	255	280	72	25.50	(1 (10 (3) 3) 3) A				
	et & has	215	280	75		A				
1040 879	724,5	210	285	70						
			િ ભ							
						197.3 J				
				<u> </u>						
Production ra	te during test					William Commence				
Oil:BOPD based on			i on	Bbls. inHoursGravGOR						
Gas: 4	40	MCFI	PD; Tested thru	(Orifice or M	Meter): Meter					
Completion Lower Completion Upper Completion Upper Completion Upper Completion Upper Completion Length of time shut-in Completion Lower Completion Lower Completion Lower Completion Lower Completion Lower Completion Lower Completion Commenced at (hour, data)* // 10 40 8 - 1/3 - 01 72 6 - 2										
	Hour, date shut-in		Length of time	shut-in	SI press psig	Stabilized? (Yes or No)				
201101		Length of time	shut-in	SI press. psig	Stabilized? (Yes or No)					

FLOW TEST NO. 2

d at (hour, date)	ha		Zone producing (Upper or Lowr):			
LAPSED TIME Since**	PRESS Upper Completion	URE Lower Compiletion	PROD. ZONE	REMARKS		
			·	(Y. /		
BOPD				sGravGOR		
y that the infom	Zijon herein con	tained is true and	d complete to the	bes of my knowledge.		
			577	Toph wpx No		
NAL SIGNED BY O	HAPLE T. PERVEN	_				
	MORECION, BIST, &	Date	8/17	101		
	te during test BOPD y that the inform servation Division NAL SIGNED BY O	Since** Upper Completion te during test BOPD based on MCFP Ty that the information herein con servation Division MAL SIGNED BY CHAPLE T. PERSON TY OIL & GAS INSPECTOR, DIST. 4	te during test BOPD based on	te during test BOPD based on		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadwoight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).