

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

5. Lease Designation and Serial No.
SF-078771

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

7. If Unit or CA, Agreement Designation
ROSA UNIT

8. Well Name and No.
ROSA UNIT #20A

9. API Well No.
30-039-25495

10. Field and Pool, or Exploratory Area
BLANCO MESAVERDE

11. County or Parish, State
RIO ARRIBA, NEW MEXICO

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other DRILLING OPERATIONS

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-2-95 MOL and RU. Spud surface hole at 1145 hrs 5/1/95 with spud mud and bit #1 (12-1/4", HTC, OSC). TD surface hole at 281'. Ran 7 jts. (261.74') of 9-5/8", 36# and 40#, K-55, ST&C and LT&C casing and set at 273' KB. Cementers Inc. cemented with 135 sx. (161 cu.ft.) of Cl "B" with 3% CaCl2 and 1/4# cello flake/sk. Displaced plug with 19 bbls of water. Plug down at 1830 hrs 5/1/95. Circulated 10 bbls of cement to surface.

5-3-95 Pressure test BOP & 7" casing to 1500#, held OK.

5-5-95 TD'd 8-3/4" hole at 3485'. Schlumberger ran IND/GR CDL/CNL logs. Loggers TD @ 3480'.

5-6-95 Ran 78 jts (3504.86') of 7", 20#, K-55, ST&C casing and landed @ 3485' KB. Float collar @ 3457'. BJ cemented with 405 sx (830 cu.ft.) of class "B" with 2% CaCl2, 8% gel, and 1/4# cello-flake/sk. Tailed with 160 sx (189 cu.ft.) of class "B" with 2% CaCl2 and 1/4# cello-flake/sk. Preceded cement with 30 Bbls of gel water and 20 bbls of scavenger cement. Displaced cmt with 140 bbls of water and plug down at 0945 hours 5-5-95. Circulated 5 bbls of cement to surface. Pressure test BOP and casing to 1500#, held OK. Unload hole with nitrogen, dry hole.

5-8-95 TD'd 6-1/4" hole with gas and bit #4 (6-1/4", HTC, J-33). Schlumberger ran IND/GR, CDL/SNL and temperature logs. Ran 58 jts (2585.10' of 4-1/2", 10.5#, K-55, ST&C casing and landed @ 5920' KB. Float collar @ 5876'. Top of liner hanger @ 3326'. BJ cemented with 245 sx (424 cu.ft.) of class "B" with 4% gel, 6-1/4# gilsonite/sk, and CF14 (fluid loss). Preceded cement with 20 bbls of gel water. Displaced cement with 65 bbls of water and plug down at 0215 hours 5-8-95. Set liner packoff and reversed out 20 bbls. Rig released @ 0600 hours 5-8-95.

14. I hereby certify that the foregoing is true and correct

Signed SUSAN GRIGUHN

Title CLERK

Date May 25, 1995

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

JUN 02 1995

*See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE
BY 21