## NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

Off. Conservation division AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (506) 334-6178 FAX: (506) 334-6170 http://www.roc.org/district.htm

not to
/reporting
/knge tests
/east New Mexico

و جا

Page 1 Revised 11/16/98

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

			ALAA MILXIOO		V-LLAIMGE [ES]			
operator	WPX	•	Lease Nar	ne <u>Ro</u> -	A UNIT	Well No/		
Location of	Well:Unit Letter	Sec <u>{</u>	25_Twp <u>31-</u>	<u>N</u> Rge <u>6- (</u>	<u>ぃ</u> API#30-0 <u>3<i>0</i>0</u>	392589000		
	NAME OF RESE		F PROD. r Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)			
Upper Completion	Pictures	(5)	<i>3.5</i>	ART. L.G.	TBG			
Lower Comp <del>let</del> ion	MESA V	<u>C</u>	85	A87.1.27	257			
		PRE	-FLOW SHUT-I	N PRESSUR	E DATA			
Upper Completion	Hour, date shut-in		Length of time		SI press. Psig	Stabilized? (Yes or No)		
	1045 2-3-01		7-	۲ ا	780	Xes		
Lower	Hour, date shut-in		Length of time		SI press, Psig	Stabilized? (Yes or No)		
Comp <del>letion</del>	1045 8.3-01		7>		230	xes		
			FLOW TE			/		
Commenced at (	(hour, date)* 1045	8-6-0	)\ .	Zone producing	(Upper or Lower): UPPE	~ 35 27 20 a		
TIME (hour,date)	LAPSED TIME SINCE*	PRESSURE Upper Completion Lower Completion		PROD. ZONI TEMP.		ALLO ALLO		
1045 8-7	24 three	388	242	730	<u> </u>	2007		
1045 8-8	48 HRS	424	258	380	· (22			
10458-9	72 Aps	310	241	01,	No.			
1045 8.10	96 Hors	1311	265	78°	BCEW MV	BCEW MV LOCIERN TIBG		
10458-11	120 485	241				SI PC FOR 2 nd Build-up		
	100 HES	371	<i>2</i> 67	90°	SI PC FOR	2 - Build - 40		
Production ra	ate during test	5 11	267	90	SI PC FOR,	2 "Buito - 40		
Production ra			<i>3€</i> 7					
		BOPD based		Bbls. in	HoursGra			
Oil:	ate during test	BOPD based	d on PD; Tested thru	Bbls. in (Orifice or M	HoursGrave_			
Oil:	ate during test	BOPD based	d on	Bbls. in (Orifice or M	HoursGrave_			

(Continue on reverse side)

FLOW TEST NO. 2

Commence	d at (hour, date)	8-16		Zone producing (Upper or Lowr): Upper				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS			
8-17	24	138	201	90	Pr inged			
8-18	72	140	285 290	f C	, ,			
		based onMCFF		. inHours Orfice or Meter):	sGravGOR			
Approved Mexico Oil Con	ALIVE 2 O	2001 19		OperatorBrooks				
By	BAIY ON 4 4X	S HASS SECTION AND A				-		
				ER LEAVAGE TEST IA		-		

- (ICO PACKER LEAKAGE TEST INSTRUCTIONS
- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: Immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).