NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Completion

Page 1

Revised 11/16/98 NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST Operator W. Iliams Production Lease Name Rosa Well No 160 Location of Well: Unit Letter O Sec 25 Twp 3/N Rge6W API#30-0 392589000 NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD.MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper PICTURES CLIFTS Completion Lower Completion MESA VERDE PRE-FLOW SHUT-IN PRESSURE DATA Hour, date shut-in Length of time shut-in Upper Stabilized? (Yes or No) Completion 5-6-02 0950 JJ411 Hour, date shut-in Length of time shut-in Lower 5-6.00 Completion 7 2 HOZ 0950 FLOW TEST NO. 1 Commenced at (hour, date)* 10 2 2 5-9-02 Zone producing (Upper or Lower): UPPER TIME LAPSED TIME PRESSURE PROD. ZONE REMARKS (hour,date) SINCE: TEMP. Upper Completion Lower Completion 240 1005 193 1450 -48 Ha-125 69 àЮ 221 1005 5-12 118 68° 72HB Production rate during test BOPD based on _____Bbls. in ___Hours ____Grav. ____GOR Oil: 130 Gas: MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper four, date shut-in Length of time shut-in SI press psig Stabilized? (Yes or No) Completion Hour, date shut-in Lower Length of time shut-in SI press. psig Stabilized? (Yes or No)

FLOW TEST NO. 2

•

Commenced at (hour, date)**				Zone producing (Upper or Lowr):		
TIME (hour,date)				PROD. ZONE	REMARKS	
						
					,	
· · · · · · · · · · · · · · · · ·						
						· · · · · · · · · · · · · · · · · · ·
Production ra	te during test	<u> </u>		<u> </u>		
Oil:	BOPD based on Bbls. in Hours, Grav. GOR MCFPD:Tested thru (Orfice or Meter):					
Remarks:		·	T D. Footod IIII d	·		
I hereby certi	ify that the infor	mation herein co	ntained is true a	nd complete to the	e bes of my knowledge.	
Approved 20 20 New Mexico Oil Conservation Division			Operat	or <u>wp</u>	4.14.125 ECL	
ن يام ^{ال} ونش ب	to an object the		Ву _	30 110	evers	
Ву			Title _	PROD T	Ech	
Title	Provide the second		Date -	5-17-0		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial

packer leakage test, a gas well is being flowed to the almosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).