

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN
DUPLICATE

(See other instructions on
reverse side)

FORM APPROVED
OMB NO. 1004-0137
Expires: February 28, 1995


WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: ☐ OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____
b. TYPE OF COMPLETION:
☒ NEW WELL ☐ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER _____

2. NAME OF OPERATOR
WILLIAMS PRODUCTION COMPANY

3. ADDRESS AND TELEPHONE NO.
P.O. BOX 3102 MS 37-2 TULSA, OK 74101 (918) 593-6254

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)
At Surface: 880' FNL & 260' FWL
At top production interval reported below :
At total depth:



5. LEASE DESIGNATION AND LEASE NO.
SF-078764

6. IF INDIAN, ALLOTTEE OR

7. UNIT AGREEMENT NAME
ROSA UNIT

8. FARM OR LEASE NAME, WELL NO.
ROSA UNIT #22A

9. API WELL NO.
30-039-26390

10. FIELD AND POOL, OR WILDCAT
BLANCO MV

11. SEC., T.R.M., OR BLOCK AND
SURVEY OR AREA
NE/4 NW/4 SEC 18-31N-5W

12. COUNTY OR
RIO ARriba

13. STATE
NEW MEXICO

15. DATE
SPUDDED
06/29/2000

16. DATE T.D.
REACHED
07/07/2000

17. DATE COMPLETED (READY TO PRODUCE)
08/04/2000

14. PERMIT NO.
DATE ISSUED
6515' GR

20. TOTAL DEPTH, MD & TVD
6290' MD

21. PLUG, BACK T.D., MD & TVD
6200' MD

22. IF MULTICOMP.,
HOW MANY

23. INTERVALS
DRILLED BY

19. ELEVATION CASINGHEAD

ROTARY TOOLS
x

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*
BLANCO MV 4821' - 6092'

25. WAS DIRECTIONAL SURVEY MADE
YES

26. TYPE ELECTRIC AND OTHER LOGS RUN
IND/GR & DEN/NEU/TEMP

27. WAS WELL CORED
NO

28. CASING REPORT (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9-5/8" K-55	36#	277'	12-1/4"	130 SX - SURFACE	
7" K-55	20#	3858'	8-3/4"	615 SX - SURFACE	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4-1/2"	3748'	6290'	280 SX		2-3/8"	6065'	

31. PERFORATION RECORD (Interval, size, and number)

CH/Menefee: 4821', 24', 27', 26', 34', 78', 5363', 82', 5426', 5556', 96', 96', 5601', 30', 54', 57', 60', 64', 67', 70', 73', 75', 84', 86', 89', 92', 96', 98', 5790' and 93'. Total of 30 (0.38") holes
Point Lookout: 5837', 39', 42', 45', 48', 51', 57', 59', 61', 64', 67', 72', 75', 77', 81', 86', 88', 91', 95', 98', 5907', 09', 15', 17', 19', 36', 39', 41', 49', 52', 66', 6060', 90' and 92'. Total of 34 (0.38") holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4821'- 5793'	80,000# 20/40 Sand in 1926 BBIs slick water
5837'- 6092'	80,000# 20/40 Sand in 1933 BBIs slick water

33. PRODUCTION

DATE OF FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping-size and type of pump) Flowing				WELL STATUS (PRODUCING OR SI) SI waiting on pipeline	
DATE OF TEST	TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL - BBL	GAS - MCF	WATER - BBL	GAS-OIL RATIO
8/08/00	3 hr	3/4"			422		
FLOW TBG PRESS	CASING PRESSURE	CALCULATED 24-HOUR RATE		OIL - BBL	GAS - MCF	WATER - BBL	OIL GRAVITY-API (CORR.)
255	855				3,378		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.): TO BE SOLD

TEST WITNESSED BY: CHIK CHARLEY

35. LIST OF ATTACHMENTS: SUMMARY OF POROUS ZONES, WELLBORE DIAGRAM

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Tracy Rees

TITLE Production Analyst

DATE

August 10, 2000

ACCEPTED FOR RECORD

AUG 23 2000

ARMINGTON FIELD OFFICE
BY *[Signature]*

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):					38 GEOLOGIC MARKERS			
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP			
					NAME	MEASURED DEPTH	TRUE VERTICAL DEPTH	
FRUITLAND	3116'	3386'						
PICTURED CLIFFS	3386'	3674'						
LEWIS	3674'	5595'						
CLIFF HOUSE	5595'	5624'						
MENEFEE	5624'	5836'						
POINT LOOKOUT	5836'							

ROSA UNIT #22A
BLANCO MESAVERDE

Location:

880' FNL and 260' FWL
NE/4 NW/4 Sec 18(C), T31N R05W
Rio Arriba, New Mexico
Elevation: 6515' GR

Spud date : 6/29/00


Completed: 8/04/00

<u>Top</u>	<u>Depth</u>
Pictured Cliffs	3386'
Lewis	3674'
CliffHouse	5595'
Menefee	5624'
Point Lookout	5836'

STIMULATION

CliffHouse/Menefee: 4821' - 5793'
(30, 0.38" holes) Frac with 80,000#
20/40 sand in 1926 bbls slick water.

Point Lookout: 5837' - 6092' (34,
0.38" holes) Frac with 80,000# 20/40
sand in 1933 bbls slick water.



Hole Size	Casing	Cement	Volume	Top Of CMT
12-1/4"	9-5/8", 36#	130 sx	176 cu. ft.	surface
8-3/4"	7", 20#	615 sx	1158 cu. ft.	surface
6-1/4"	4-1/2", 10.5#	280 sx	406 cu. ft.	3748'