

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Pubco Development Inc.  
(Company or Operator)

State  
(Lease)

Well No. 14, in NW 1/4 of SW 1/4, of Sec 36, T 30, R 9W, NMPM.  
Blanco Pool, San Juan County.  
Well is 1700 feet from South line and 990 feet from West line  
of Section 36. If State Land the Oil and Gas Lease No. is E-5315, E-11479, E-1641  
Drilling Commenced 6-22, 1953. Drilling was Completed 7-11, 1953.  
Name of Drilling Contractor George Moland Drilling Co.  
Address 624 South Cheyene, Tulsa 3, Oklahoma  
Elevation above sea level at Top of Tubing Head 5756. The information given is to be kept confidential until  
19.


Gas  
SANDS OR ZONES

No. 1, from 4026 to 4810 No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.



CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10 3/4	32.75	New	189	Howco			
7	20 & 23	New	3972	Baker			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15	10 3/4	189	170	Howco		
9	7	3972	200	Howco		
	2	4777				

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Shot with 2050 qts. SNG from 4042 to 4813.  
Result of Production Stimulation IP 4,830 MCF 3 hr. open flow through tubing;  
Shut in casing pressure 1055#; Shut in 11 days.  
Depth Cleaned Out 4810

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 4810 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19  
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was  
was oil; % was emulsion; % water; and % was sediment. A.P.I.  
Gravity  
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of  
liquid Hydrocarbon. Shut in Pressure lbs.  
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy	T. Devonian	T. Ojo-Alamo			
T. Salt	T. Silurian	T. Kirtland-Fruitland	2140		
B. Salt	T. Montoya	T. Farmington			
T. Yates	T. Simpson	T. Pictured Cliffs	2447		
T. 7 Rivers	T. McKee	T. Menefee	4214		
T. Queen	T. Ellenburger	T. Point Lookout	4630		
T. Grayburg	T. Gr. Wash	T. Mancos	4795		
T. San Andres	T. Granite	T. Dakota			
T. Glorieta	T.	T. Morrison			
T. Drinkard	T.	T. Penn			
T. Tubbs	T.	T.			
T. Abo	T.	T.			
T. Penn	T.	T.			
T. Miss	T.	T.			

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Surface	1425	1425	Tertiary Sands & Shales				
1425	2140	715	Kirtland				
2140	2447	307	Fruitland				
2447	2548	101	Pictured Cliffs				
2548	4026	1478	Lewis				
4026	4214	188	Cliffhouse				
4214	4630	416	Menefee				
4630	4795	165	Point Lookout				
	TD	4810					

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

7-30-53 (Date)  
Company or Operator Pubco Development Inc. Address Box 844, Aztec, New Mexico  
Name Charles S. Peters Position or Title District Geologist