



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **078385**
Unit **Thompson**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			
Notice of Intention to re-work	X		

RECEIVED
JUL 7 1961
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. **2** is located **990** ft. from **S** line and **990** ft. from **W** line of sec. **34**
SW Section 34 **30-N 8-W** **S.M.P.M.**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesa Verde **San Juan** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6342** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging, etc., including points, and all other important proposed work)

It is intended to workover this well in the following manner:

1. Pull tubing, make trip with bit to 4670'.
2. Set bridge plug at approximately 4600'.
3. Attempt to clean out to bridge plug using gas. If well dries up run Lane Wells Potential Survey and McCullough Magnetic Survey. If surveys show that casing is extremely bad, run free point, cut and pull 7" casing, for inspection.
4. If well does not dry up, run McCullough Magnetic Survey, cut and pull casing if survey warrants such action.
5. Mud up and condition open hole.
6. Run new 7" casing with casing bowl.
7. Clean out to bridge plug and test casing to 2000 psi. Squeeze if necessary.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**
 Address **Box 990**
Farmington, New Mexico

Original Signed **D. W. Meehan**
 By _____
 Title **Petroleum Engineer**

Workover Procedure

8. Drill bridge plug and clean out to total depth.
9. Run tubing.