

COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.  
B-11479-22

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator Pueblo Petroleum Corporation	7. Unit Agreement Name
2. Address of Operator Post Office Box 869, Albuquerque, New Mexico 87103	8. Name of Leasee Delhi State
3. Location of Well UNIT LETTER I 1800 FEET FROM THE south LINE AND 890 FEET FROM T10S CASE LINE, SECTION 36 TOWNSHIP 30N RANGE 9W NMPM.	9. Well No. #1
10. Field and Pool, or Willam Blanco Pictured Cliff	
11. Elevation (Show whether DF, RT, GR, etc.) 5847 Gr.	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was damaged by fresh water from a casing leak at 1,063'.  
The well was plugged and abandoned as follows:

1. Squeezed perforations at 2524-46' with 50 sacks. Class C neat.
2. Set 50 sx. plug in 4-1/2" casing from 1200' to 500'.
3. Squeezed 25 sx. through hole in casing at 1063'.
4. Squeezed Bradenhead with 25 sx. Class C neat.
5. Set dry hole marker at surface.

NOTE: No casing recovery was attempted.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald C. Walker C. Walker TITLE District Engineer DATE January 10, 1969

APPROVED BY Emory Clumet TITLE Sup Dist III DATE 1-14-69

CONDITIONS OF APPROVAL, IF ANY:  
Refer Forate to Squeeze 200 sacks  
From 500 feet to surface