

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
**Ladd Petroleum Corporation**

3. ADDRESS OF OPERATOR  
**830 Denver Club Building, Denver, CO 80202**

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☒

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

**NM 0206995**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

**Aztec**

9. WELL NO.

**2-35**

10. FIELD OR WILDCAT NAME

**Basin Dakota**

11. SEC., T., R., M., OR BLK. AND SURVEY OR  
**35E30N-14W-NMPM**

12. COUNTY OR PARISH

**San Juan**


13. STATE

**New Mexico**

14. API NO.

15. ELEVATIONS (SHOW @, KDB, AND WD)  
**5526**

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

**Change of plans submitted 3/18/80**

1. Set 50 Sx cement plug across perms 5748'-5772' in 4 1/2" casing.
2. Set 50 Sx cement plug across Gallup zone @ 4876' in 4 1/2" casing.
3. Set 50Sx cement plug across M.V. zone @ 2700' in 4 1/2" casing.
4. Perf. and attempt to circulate across Fruitland & P.C. zones. If unsuccessful, set 250' cement plug across perf.
5. Set 10Sx cement plug @ surface, weld plate and install marker.
6. Comply with surface restoration stipulations as contained in B/M letter to USGS regarding subject well dated 1/25/80.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct District

SIGNED Chyle D. Healy TITLE Superintendent DATE May 12, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

**APPROVED**

JUN 4 1980

JAMES F. SIMS

DISTRICT OIL & GAS SUPERVISOR

NMOCC