MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Beain Dakota				Formation Daketa				County San June			
Ini	tial	Ann	ual		Speci	al		_Date of 1	est	4-63	
Com	pany	ion Potrol	on Cor	constic	ease <u>Car</u>	son Gas	Unit	Wel]	No	<u> </u>	
Uni	t <u> </u>	ec. 32 T	wp 36	Rge	· 124	Purcl	naser				
		-	-			Perf. 6060 To 6072					
Tubing 2 1/2 Wt. 1.7 I.D. 1.995 Set at 6053 Perf. To											
Gas Pay: From 6060 To 6072 L 6066 xG 700 Fet -GL 4266 Bar. Press. 12											
Producing Thru: Casing Tubing Y Type Well Single-Bradenhead-G. G. or G.O. Dual											
Date	e of Complet	ion:	-63	Single-Bra Packerstone Reser			gle-Brade Reservo	denhe ad-G. G. or G.O. Dual voir Temp			
	_				OBSERVE		_	~			
Tested Through (Choke) (Choke) (Type Taps Flags											
			Data		T	Tubing	Data	Casing Da			
,,,		(Choke)	Press.	Diff.	Temp.	Press.	Temp.	Press.	Temp.	Duration	
No.	(Line) Size	(Orifice) Size	psig	h _w	°F.	psig	°F.	psig	°F.	of Flow Hr.	
SI	A Days	800				2029	70 _{East}	2023		4 9	
1. 2.	211	.750	273			303		930		3 Honra	
3.											
4. 5.		<u> </u>							· · · · · ·		
No.	Coefficient (24-Hour) √		Pressure				Gravity	Compress. Factor Fpv		O MORROD	
1.	12.3650		385		1,0000		,9258	1.033 3371		3371	
2. 3.							 				
4. 5.											
PRESSURE CALCULATIONS Gas Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Gravity of Liquid Hydrocarbons deg. Specific Gravity Flowing Fluid Fc (1-e^-s) P_c_4_165_461											
No.	P _w Pt (psia)	Pt ²	F _c Q	$(F_cQ)^2$	(F.	Q) ²	P _w 2	$P_c^2 - P_w^2$	Ca.	1. Pw Pc	
1.	76 (psia)				(1)	, ,	87, 34,	3, 276, 317		W	
2. 3.					_				 		
4.											
ADDI AGEI WIT	olute Potent PANY Pen ARRESS Box ASC NT and TITLE NESSED	rieno Petr	eleum Co		26	n_0.7	741/		FIVE		
COM	PANY				REM	ARKS		OII	CON.	CUM,	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w). MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_{t-} Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_W cannot be taken because of manner of completion or condition of well, then P_W must be calculated by adding the pressure drop due to friction within the flow string to P_+ .