

Submit 3 Copies
to Appropriate
District Office

3 NMCCD
1 File

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1730, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2038
Santa Fe, New Mexico 87504-2038

WELL API NO.

30 045 08994

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

B-11571

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Dugan Production Corp.

3. Address of Operator

P.O. Box 420, Farmington, NM 87499

4. Well Location

Unit Letter K : 1650 Feet From The South Line and 1650 Feet From The West Line

Section 36 Township 30 N Range 14 W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

5592' GL

7. Lease Name or Unit Agreement Name

Stella Needs a Com

8. Well No.

1

9. Pool name or Wildcat

Basin Dakota

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: P&A Dakota, convert to SWD service ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to plug and abandon Dakota and Gallup as follows:

1. Spot class "B" cement across Dakota top (5850') from 5800' - 5900'.
2. Perforate 50' below Gallup top (4992'). Place 100' cement plug inside and outside casing.

Prepare well for conversion to salt water disposal in the Mesaverde as follows:

1. Set cement plug inside and outside casing at top of Mancos Shale (4027').
2. Perforate above Cliffhouse and circulate cement to surface.
3. Perforate selected zones in the Cliffhouse and Point Lookout.
4. Swab and collect water samples to determine water quality.
5. Apply for injection into all zones within the Mesaverde.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

John Alexander

TITLE Vice-president

DATE 11/18/99

TYPE OR PRINT NAME

John Alexander

TELEPHONE NO. (505) 325-1821

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY RONIE BUSCH

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEPUTY OIL & GAS INSPECTOR, DIST. 42

NOV 23 1999