

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 37 078213

Unit 1/2 Sec. 35, T-30N,
R-13W, N.M.P.M., San Juan
Co., New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 9, 19 63

City of Farmington
Well No. 2-35/ is located 2510 ft. from S line and 790 ft. from W line of sec. 35

SW 3/4 Sec. 35
(1/4 Sec. and Sec. No.)

10-N
(Twp.)

13-W
(Range)

N.M.P.M.
(Meridian)

San Juan
(Field)

San Juan
(County or Subdivision)

N.M.
(State or Territory)

The elevation of the derrick floor above sea level is 5628 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Drilled to T.D. of 6373 ft. with mud.
2. Ran 197 jts. 4-1/2", O.D., 10.50#, J-55 casing. Landed at 6369 H.K.B. Float collar at 6358'.
3. Cemented with 200 cu. ft. 50-50 pounds w/6% gel, 1/8" Jal Flake and 10% salt/sk with 1/2% TIC., follow with 200 cu. ft. 50-50 pounds w/2% gel, 1/8" gel Flake and 10% salt/sk. w/1/2% TIC. Tailed in w/75 sks. Regular Latex. Plug down 12:35 A.M. 12-19-62. Good circulation throughout job.
4. Cleaned out to P.B.T.D. of 6358' HKB. Pressure tested casing to 3500 psi for 30 minutes.
5. Circulate hole w/1% CaCl₂ water. Spot 500 gal. 15% Acid. Perf. 1 hole/ft. As following depths: 6345-6337, 6334, 6285, 6257, 6291, 6293, 6257, 6255, 6252, 6250, 6248, 6241, 6239, 6237, 6234, 6217, 6215, 6213, 6165, 6160, 6157, 6154, 6149.
(OVER)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SOUTHERN UNION PRODUCTION COMPANY

Address P. O. Box 808


Farmington, New Mexico

By

D. G. Hagg

Title

Petroleum Engineer



Sand/Water fraced with 120,000# 20-40 sand and 101,300 gallons 1% CaCl_2 Water. Spearhead w/1000 gal 1% HCl.

6. Cleaned out to P.S.T.D. of 6350' RKB.
7. Ran 195 fts., 1-1/2" tubing. Landed @ 6240' RKB.
8. Well completed 12-24-62.