Revised 12-1-55

MULTI-POINT	BACK	PRESSURE	TEST	FOR	GAS	WELLS
-------------	------	----------	------	-----	-----	-------

Pool Underlanded Pekots				F	Formation				County			
Init	tial		_Annu	al	Special				Date of Test			
Comp	pany bolh i	-Taylo	r 011	Corpo	oration Lease induick			ek	Wel	2		
Unit	RE/4 S	Sec	Tw	p	Rg_Rg	e. <u>10-1</u>	Purc	haser				
Casi	ing 5-1/3 " W	/t <u>17</u> /	<u></u> I	.D. 4.1	92 Se	t at 71	46 Pe	rf64	96	То	7064	
Tubi	ing • W	t. 4.7	I	.D. <u>l.</u>	98 _Se	tat <u> </u>	000 Pe	rf. Com	ended	To		
Gas	Pay: From_	6896	To_ 7 (266	L	x	G			Bar.Pr	ess. <u>1</u>	
Prod	lucing Thru:	Casi	ing		Tu	bing	<u> </u>	Type We	11	ngle g		
Date	e of Complet	ion:	7-19	-60	Packe	r Son	Sin	gle-Brade Reservo	enhead-G.	G. or (G.O. Dual	
							ED DATA					
Test	ed Through	(Prove) ((Choke)	(Motor)				Type Tap	s		
			Low Da				Tubing	Data	Casing Da	ata	<u> </u>	
No.	(Prover) (Line)	(Chol	ke) ice)	Press	J I				Press.	ļ	of Flow	
- 1	Size	Siz	ze	psig	h _w	°F•	psig	°F.	psig		Hr.	
SI l.		3/4	44	19		284	1831	440	2064 881	444	7 Sans	
2.		- 9/		<u> </u>			740	9,5	444	79	2 0000	
<u>3. </u>												
4. 5.												
					1	TIOW CAT	CHT.ATTON:	S				
	Coefficient Press				essure	FLOW CALCULATIONS ssure Flow Temp. Grav		Gravity	ity Compress. Rate of Flow			
No.	(24-Hour) $\sqrt{h_W}$		hur	i J		Fac F	tor	Factor F _g	Factor		Q-MCFPD @ 15.025 psia	
1.	12.363		γ w ₁	297		0.9741		0.9721			2660	
2.												
3 c 4 •												
5。												
					PRI	ESSURE C	ALCUTATIO	ONS				
as L	iquid Hydro	carbon	Ratio)		cf/bbl.		Sneci	fic Gravit	tv Sena	arator Gas	
	ty of Liqui		carbo	ns_		deg.		Speci	fic Gravit	y Flow	ving Fluid	
c			(]	_e ^{_s})				^Р с—	1043	_Pc	3, 394, 649	
- 1	n I	 -								+		
No.	$P_{\mathbf{W}}$	P _t .	F	Q.	$(F_cQ)^2$	(F	c ^{Q)2}	P _w 2	$P_c^2 - P_w^2$	Ca	Pw	
\downarrow	Pt (psia)					(1	_e-s)	~	"	I	Pw Pc	
<u>1•</u> − 2. −										 		
1. 2. 3. 4.												
4. 5.												
	lute Potent	ial:		2962		MCFPD;	n	0.75				
COMP	ANY Dell	1-167			PARTIES.	, 160 H						
ADDR AGEN	T and TITLE					Police		13	Ly mac			
WITN	ESSED_	Rights			Congressy							
COMP	ANI				7,7	REM	ARKS					
			-						CCL	1		

SEP 27 1960 OIL CON. COM. DIST. 3

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- . n I Slope of back pressure curve.

Note: If P_{W} cannot be taken because of manner of completion or condition of well, then P_{W} must be calculated by adding the pressure drop due to friction within the flow string to P_{+} .

STATE OF ME.I MEXICO

OIL CIRE EVATION DAMESSIO

DIT OFFICE

IF ASSET OF OUR STATEMENT OF THE STATEMENT OF T