	I

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122
Revised 12-1-55

MULTI-POINT	BACK	PRESSURE	TEST	FOR	GAS	WELLS

ool	Blano) [1	oture	d Clif	fs	_Formatio	n let	ured C	liffe	County_	en Ju	en .
nit	ial	X		Annu	ual		Sp e	cial		Date of	Test_9	eptember 25, 1
omp	any an	Ame	rican	etro	Louis	Corporat	ionase 1	liott (Cas Unit "I	We	ll No	1
nit	A		Sec	33 Tw	љ	30 N F	ige	Pu	ırchaser 👊	Paso Natu	ural Ga	e Company
si	ng 4–1/	544 N	/t	7.5 I	.D	4.050 S	Set at 2	573	Perf. 2443	-2449	To_	
									Perf. oper			
									ost _GL]			
te	of Com	plet	ion:	9/17/	/61	Pack	er No	S	Type Weingle-Brade	enhead-G.	G. or	G.O. Dual
										ori remb.	A.A.U.	
			A-11-1-1-1	Provide /				ED DAT	A			
st.	ed Thro	ugh				(MEEEE	<u>9</u>			Type Tar	os	
Т	(Prov	er)		Flow Da oke)		s. Diff	. Temp.		ng Data s. Temp.	Casing I	Data	Duration
\cdot	`(Lin Siz	e)	(Ori:	fice)			1			psig		I of Flor
╁			L	lays		g h _w		psi,	g r.	957	J.F.	Hr.
_	2-inel			inch			60 eet		60 est	668	60 es	3 hrs
t												
+												
							FLOW CAL	ርነπ.ልጥፐ(าพร		·· · · · · · · · · · · · · · · · · · ·	
	Coef	ici	ent			Pressure	Flow	Temp.	Gravity			Rate of Flow
		o _f			tor t				Q-MCFPD 9 15.025 psia			
F	12.3	5				566	1,0			1,07		6952
						PI	RESSURE CA	alcui at	TIONS			
Li	auid Hy	rdro	arbon	Ratio)		cf/bbl.		Sneci	fic Gravi	t⊽ Sens	arator Gas
it	y of Li	quic	l Hydr	ocarbo	ns -e-s		deg.		Speci	fic Gravi	ty Flow	ving Fluid
				(1	L -e - <u>,</u>	<u> </u>			^P c	969	_ ^F c	738,961
	P _w					, , ,	,] .			2 0		
	Pt (psi	.a)	$P_{\mathbf{t}}^2$	Fc	Q	(F _c Q) ²	(F ₁	Q) ² -e-s)	P _w 2	$P_c^2 - P_w^2$	Ca	Pw Pc
						-			462,400	476,561	1	
_						ļ <u></u>						
-											 	
	ute Pot				,375		MCFPD;	n_ @	.85			
Œ	SS Door	480,	Pare	dagton	, Ken	orporet!						
T	and TI SSED	TLE	R. M	. Bene	r, h	r. Se	mlor Peti	olom	Engineer	Kulsa	and)	ATILA
	NY			· · · · · · · · · · · · · · · · · · ·							10	ATHIN)
							REMA	RKS			1	LUL 1 10E1
											\ (CT11 1961
											/o	IL CON. OF
											\	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt- Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}^{-}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

.2

A TA