

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL and 1650' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF-078139-

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Sandoval Gas Com "A"

9. WELL NO.

10. FIELD OR WILDCAT NAME
Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NW/4, NE/4, Section 35, T30N, R9W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.
30-045-09038

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5703' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NM

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This is to confirm verbal approval Beecher/Kadillak on 8/28/80 to plug and abandon the subject well as follows:

1. Set a permanent bridge plug at 4400'.
 2. Set a cement retainer at 3800'.
 3. Squeeze and plug the Cliffhouse Mesaverde Formation (4008'-4368') with 100 sacks Class "B" Neat cement.
 4. Plug Pictured Cliffs (2340'-2450') with 25 sx Class "B" Neat cement.
 5. Plug the Ojo Alamo (1330'-1360') with 25 sx Class "B" Neat cement.
 6. Plug surface with 20 sx Class "B" Neat cement.
- Spot 9.0 PPG mud between plugs. Clean up location and install a PXA marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. A. Hounney TITLE District Engineer DATE September 9, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE APPROVED

CONDITIONS OF APPROVAL, IF ANY:

al Buck

AMOCO

*See Instructions on Reverse Side

SEP 15 1980
JAMES F. SIMS
DISTRICT OIL & GAS SUPERVISOR