

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
5. Indicate Type of Lease
STATE ☐ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Wagoner

8. Well No.

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK OR A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
B. M. N. S. Company - NMOCN

3. Address of Operator
1000 Rio Brazos Rd, Aztec, NM 87410 334-6178

4. Well Location
Unit Letter C : 660 Feet From The North Line and 2320 Feet From The West Line
Section 32 Township 30 N Range 12 W NMPM County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: ☐	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moh & RV Rig: No Tubing IN Hole, R.H. by 5 1/2" Gauge Ring and Tagged Something at 1227' R.H. with 2 3/8" Tubing to 1578'. Circulate Hole clean with water. Plug #1 (1249'-1578') Below 40SXCL.B. Cement Plug, WOC & Tagged YOC at 1249', POH, Perforated at 1127', Set Retainer at 1052', Plug #2 (1032-1127') Placed 40 SX Below Retainer to 1400PSI and Placed 6SXCL.B. on top of Retainer, POH. Perforated at 100', Established Injection Rate at 215 BPM with 350PSI, No Circulation to Surface. Plug #3 (0-100') Mixed 129 SX CL.B. Plug. Zero Displacement WOC. Cement to Surface. AS Cut off CSG. Installed Dry Hole Marker and Reclaimed Location.

(See Attached Report)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Nathan Crawford TITLE P&A Supervisor DATE 3-11-95
(505)
TYPE OR PRINT NAME Nathan Crawford TELEPHONE NO. 327-4961

(This space for State Use)

ORIGINAL SIGNED BY E. VILLANUEVA DEPUTY OIL & GAS INSPECTOR, DIST. III MAY 4 1995

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:



Key Energy Services, Inc.

Four Corners Division
P.O. Box 900
5651 US Highway 64
Farmington, NM 87499

Phone: 505-327-4935
Fax: 505-327-4962

PAGE 1

TO: CHARLIE PERRIN
NMOCD
1000 RIO BRAZOS RD
AZTEC, NM 87410

FROM: NATHAN CRAWFORD
KEY ENERGY SERVICE, INC.
P.O. BOX 900
FARMINGTON, NM 87499

Re: CONTRACT #99-521.25-035 "DAILY ACTIVITY REPORT"

WAGGONER #2

03-09-99 MOL AND RU RIG. ND WELL HEAD AND ATTEMPT TO POH WITH 1 1/4" TUBING. NO TUBING UNDER TUBING HANGER. RIH WITH 5 1/2" GAUGE RING AND TAGGED SOMETHING AT 1227'. RIH OPEN ENDED WITH WORK STRING TO 1578' AND DID NOT TAG ANYTHING. CIRCULATE HOLE CLEAN WITH WATER. PLUG #1 (1436' - 1578'), BALANCED 40 SX CLASS B CEMENT PLUG. POH AND WOC.

03-10-99 RIH WITH TBG AND TAGGED TOC AT 1249'. POH. RIH AND PERFORATED SQUEEZE HOLES AT 1127'. PU AND RIH WITH 5 1/2" RETAINER AND SET AT 1082'. ESTABLISHED INJECTION RATE INTO PERFORATIONS AT .5 BPM WITH 1800 PSI. MIXED 46 SX CLASS B CEMENT, PLACING 40 SX BELOW AND 6 SX ABOVE RETATINER AND SQUEEZING TO 1400 PSI. POH. RIH AND PERFORATED SQUEEZE HOLES AT 100'. ESTABLISHED INJECTION RATE INTO PERFORATIONS AT 2.5 BPM WITH 350 PSI WITH 40 BBL WATER, NO CIRCULATION WAS SEEN AT SURFACE. WAIT ON ORDERS. MIXED AND PUMPED 129 SX CLASS B CEMENT DOWN 5 1/2" CSG. PRESSURE CLIMBED UP TO 550 PSI THEN BROKE BACK. FINAL SHUT IN PRESSURE WAS 120 PSI. WOC. OPEN VALVE AND WELL DEAD. ND BOP AND CUT OFF WELL HEAD. RD AND MOL. INSTALLED DRY HOLE MARKER AND RECLAIMED LOCATION.

NEX
3-11-99