NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

: --- +

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other) Sand/Water Fracti	ring
	July 9, 1956	Farmington, New Me	xico
Following is a report on the work	done and the results obtained under the heading	noted above at the	
Delhi-Taylor Oil Corporation (Company or Operator)		Eugene Jacques (Lease)	
San Juan Drilling Contractor	pany , Well No	in the SV 1/4 SV 1/4 of	Sec25,
(======================================	Blanco Pool,	San Juan	County.
The Dates of this work were as folows:	July 3, 1956		
) submitted on Form onon	Nav 23	19 56
		(Cross out incorrect words)	, 10,
DETAI	LED ACCOUNT OF WORK DONE AND RES		gged and
DETAILS 1/2" Casing landed in 1/2" easing perform gal water and 30,000#3 ridge p lug 4160".	LED ACCOUNT OF WORK DONE AND RESEAT 4732. Cement drilled outed 4640 to 4540 w/ 200 bull sand, Pressures 1500# to 1 Perforated 4128 to 4060 w/	it to PBTD 4705. Logilets, water frac. w, 1800# Inj. 53 BPM. / 136 bullets, water	/ 39,000 Set frac. w/
DETAIL 5 1/2" Casing landed 5 1/2" easing perfora 5 1/2" easing perfora 6 1/2" easing perfora 7 1/2" easing perfora 8 1/2" easing perfora	LED ACCOUNT OF WORK DONE AND RESEAT 4732. Cement drilled outed 4640 to 4540 w/ 200 bull sand, Pressures 1500# to 1 Perforated 4128 to 4060 w/ 30,000# sand, Pressures 100	it to PBTD 4705. Logilets, water frac. w, 1800# Inj. 53 BPM. 136 bullets, water 100# to 1200# Inj.	/ 39,000 Set frac. w/
DETAILS 1/2" Casing landed to 1/2" easing perfora gal water and 30,000# B ridge p lug 4160".	LED ACCOUNT OF WORK DONE AND RESEAT 4732. Cement drilled outed 4640 to 4540 w/ 200 bull sand, Pressures 1500# to 1 Perforated 4128 to 4060 w/	it to PBTD 4705. Logilets, water frac. w, 1800# Inj. 53 BPM. 136 bullets, water 100# to 1200# Inj.	/ 39,000 Set frac. w/
DETAILS 1/2" Casing landed in 1/2" casing perform gal water and 30,000# ridge p lug 4160'. 39,000 gal water and Drilled plug and CO teres set, Well SI.	LED ACCOUNT OF WORK DONE AND RESEAT 4732. Cement drilled outed 4640 to 4540 w/ 200 bull sand, Pressures 1500# to 1 Perforated 4128 to 4060 w/ 30,000# sand, Pressures 100	it to PBTD 4705. Logilets, water frac. w. 1800# Inj. 53 BPM. 136 bullets, water 100# to 1200# Inj. 110	/ 39,000 Set frac. w/
JETAN 1/2" Casing landed 1/2" easing perform all water and 30,000# ridge p lug 4160'. 19,000 gal water and brilled plug and CO to the set, Well SI. Witnessed by	LED ACCOUNT OF WORK DONE AND RES at 4732. Cement drilled ou ted 4640 to 4540 w/ 200 bul sand, Pressures 1500# to 1 Perforated 4128 to 4060 w/ 30,000# sand, Pressures 100 o 4673. Est. 5000 MCF. 2' I hereby certify	t to PBTD 4705. Logical Logica	/ 39,000 Set frac. w/
DETAILS 1/2" Casing landed in 1/2" casing perform gal water and 30,000#3 ridge p lug 4160'. 30,000 gal water and Drilled plug and CO to the set, Well SI. Witnessed by Mr. M. L. Joh (Name)	LED ACCOUNT OF WORK DONE AND RES at 4732. Cement drilled ou ted 4640 to 4540 w/ 200 bul sand, Pressures 1500# to 1 Perforated 4128 to 4060 w/ 30,000# sand, Pressures 100 o 4673. Est. 5000 MCF. 2' mson Delhi-Taylor Oil (Company) I hereby certify to the best of m Name	at to PBTD 4705. Logarithms, water frac. w. 1800# Inj. 53 BPM. 136 bullets, water 136 bu	39,000 Set frac. w/ 53 EPM. 1958
DETAILS 1/2" Casing landed in 1/2" casing perform gal water and 30,000# Bridge p lug 4160'. 30,000 gal water and Drilled plug and CO to the set, Well SI. Witnessed by	LED ACCOUNT OF WORK DONE AND RES at 4732. Cement drilled or ted 4640 to 4540 w/ 200 bull sand, Pressures 1500# to 1 Perforated 4128 to 4060 w/ 30,000# sand, Pressures 100 o 4673. Est. 5000 MCF. 2' mson Delhi-Taylor 011 (company) I hereby certify to the best of m Name Position	t to PBTD 4705. Logical Logica	39,000 Set frac. w/ 53 BPM. 1956 DOM:

	AZTEC DETRICT OFFICE
	3 - 1891
•	- 1 2