

TENNECO Oil Co.
DURING DISTRICT
FLORANCE 3-29

1500' FSL, 3730' FEL,
SECTION 25, T. 30 N., R. 8 W.

ELEVATION:
GL 6202'
DF 6212'
ZERO 10'

DUAL COMPLETION

BLANCO MESA VERDE
BASIN DAKOTA

TUBING: 233 LBS. 2 3/8" O.D. SEAL-LOCK
LANDED AT 7320'

10 3/4" O.D., 32.75#/FT @ 178'

STAGE COLLAR @ 4118'

LEGEND

SS - SLIDING SLEEVE
LN - TYPE F LANDING NIPPLE
SA - SEAL ASSEMBLY
PT - PRODUCTION TUBE

CEMENTING RECORD - 4 1/2" CASING

1ST STAGE W/ 390 SK 50-50 POZ CLASS C
TOP ABOVE 4118'

2ND STAGE W/ 256 SK CLASS A W/ 12% GEL
TOP @ SURFACE

7" 20 & 23" @ 4685'

SDTK @ 4695'

CMT. @ 4695'

TO 5444

FRACED DAKOTA W/ 70,000 GAL KCL
WTR. & 55,000 # 20-40 SD.

DAKOTA PERFORATIONS G. R. DEPTHS

7360
7363
7467
7470
7493
7497
7501
7506
7520
7541

SS 7313
LN 7319
SA 7320
PT 7324

MESA VERDE PERFORATIONS G. R. DEPTHS

4788	FRAC 2 ND STAGE W/
4795 1/2	100,000 GAL. KCL WTR.,
4802 1/2	70,000 # 10-20 SD, & 5000 #
4852	B-12 SD.
4858 1/2	
4867 1/2	
4884 1/2	
4925 1/2	
5019	
5225	FRAC 1 ST STAGE W/
5240 1/2	100,000 GAL KCL WTR.,
5249 1/2	70,000 # 10-20 SD &
5261 1/2	5000 # B-12 SD.
5275	
5291	
5307 1/2	
5326 1/2	
5339	

BAKER MODEL D
SET @ 7320'

PSTD - 7638'

4 1/2" O.D., 10.5 #/FT @ 6620'
4 1/2" O.D., 11.6 #/FT @ 7680'

