## UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES	5. LEASE 1994 6 596	$\neg$
DEPARTMENT OF THE INTERIOR	5. LEASE 119 11 11 11 11 11 11 11 11 11 11 11 11	/
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	+-
GEOLOGICAL SURVEY	[ 문문학원 - 첫 - 글 글 프 - ]	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME:	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		
Teservoll, Ose Folia 5-331-0 for such proposers.	8. FARM OR LEASE NAME	
1. oil gas 🔀 other	E. E. Elliott "A" & S	
Well Well Odlet	9. WELL NO.	
2. NAME OF OPERATOR	5 2 2 5 6 £	
AMOCO PRODUCTION COMPANY	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Blanco Pictured Cliffs	
501 Airport Drive Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY	OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA SE/4 SE/4 Section 15	,
below.) 1130' FSL x 990' FEL, Section 15,	T-30-N, R-9-W = 3 3	
AT SURFACE: $T-30-N$ , $R-9-W$	12. COUNTY OR PARISH 13. STATE 5	
AT TOP PROD. INTERVÁL: Same	San Juan See S NM See	
AT TOTAL DEPTH: Same	14. API NO. 200 7 5 7 7	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-045-09446 985	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND W	<u></u>
,	6179 LGL	נטו
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		_
TEST WATER SHUT-OFF	inger but in service of the control	
FRACTURE TREAT	10 Page 1	
SHOOT OR ACIDIZE		
REPAIR WELL	(NOTE: Report results of multiple completion or zo	one
PULL OR ALTER CASING	change on Form 9–330.) It is to be a position to the control of th	ď
MULTIPLE COMPLETE		<u>ĕ</u> .
ABANDON*		ž
(other)	그 그는 그는 의사를 위한 함께 하는 회사를 하는 것이다.	enoibunte
	그 기계	1
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	e all pertinent details, and give pertinent dat	es,
including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinen	irectionally drilled, give subsurface locations a	and
Operations commenced on 4/7/78. Tripped out	with tubing. Tripped in with	
tubing, bit and casing scrapper. Cleaned out	to 2975' PBD = Fraced down	
casing with 200,000 pounds sand and 100,000 g	allons frac fluid. Flushed	
_	##Daa 1 2 2 2 2	
well.		
Set 1-1/4" production tubing. Tubing landed	at 2940 · 如何有	
. 10 - 1 - 0	🚤 នាងស្គីស្គី គំ ជាំស្គីគ្នា	
Rig released on 4/11/78.		
	Restaurant de l'appear	
	1078 \$ 555 \$ 556 \$ 556 \$	
	필요한 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등	
	· COM·	
O L COCK Value Many and Tune	3 \ 1922 3 3 3 3	
Subsurface Safety Valve: Manu. and Type	ST W	Ft.
18. I hereby certify that the foregoing is true and correct		
The state of the s	8/18/78 CALL	
SIGNED TITLE Adm. Supervis	DATE	
(This space for Federal or State offi	ce use)	
( apass 15 casts. of state offi		
APPROVED BY TITLE	DATE	
CONDITIONS OF APPROVAL, IF ANY:	중공부원형 우리 실립질률	
	១០១៩ឆ្នាំ ខ្នាំ ទីម <b>់</b> ព	
	프로뉴트 및 기계	