

			6
1			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. N.M.-06375
Unit 1/2, Sec. 1, T-30N,
R-13W, N.M.P.M. San Juan
City, New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	☒	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 29, 19 60

Well No. 1-4 is located 770 ft. from [N] line and 290 ft. from [E] line of sec. 1
NE 1/4, NE 1/4, Sec. 1 T-30N R-13W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Rasin Dakota San Juan County New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5889 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging, cementing points, and all other important proposed work)

We propose to:

1. Complete Dakota formation as stated on original "Intent to Drill" filed November 25, 1960.
2. In addition we propose to test the Gallup formation in the following manner.
A. Perf. Gallup formation approx. 5960-5980.
B. Sand & Oil Free with approx. 50,000# 20-40 sand.
3. If Gallup is found productive we propose to dual complete well in the following manner.

(OVER)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SOUTHERN SLOAN GAS COMPANY

Address P. O. Box 808
Farmington, New Mexico

By Gilbert D. Roland Jr.
Gilbert D. Roland, Jr.
Title Drilling Superintendent

- A. Set Baker $1\frac{1}{2}$ " Cast Iron Model "IP" production packer at approx. depth 6530' H.K.B.
- B. Run 2" E.O.E. Tbg. w/Cross-over sub assembly and Baker Model "EXD" $1\frac{1}{2}$ " retrievable packer. Set Packer at approx. depth of 5800' H.K.B.
- C. Produce Dakota formation from Annulus between $1\frac{1}{2}$ " Cag. & 2" E.O.E. Tbg.
- D. Produce Gallup from 2" E.O.E. Tbg.