



NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Pan American Petroleum Corporation
(Company or Operator)

E. Tharland
(Lessee)

Well No. 1, in NE $\frac{1}{4}$ of NE $\frac{1}{4}$ of Sec. 6, T. -30-N, R. -15-W, NMPM.
Verde-Gallup Pool, San Juan County.
Well is 560 feet from North line and 660 feet from East line

of Section 6. If State Land the Oil and Gas Lease No. is _____
Drilling Commenced June 1, 1957 Drilling was Completed July 12, 1957

Name of Drilling Contractor Sage Drilling Company

Address Box 788, San Angelo, Texas

Elevation above sea level at Top of Tubing Head Ground Level 5354' The information given is to be kept confidential until
Not confidential, 19____

OIL SANDS OR ZONES

No. 1, from 2040 to 2170 oil No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from none to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.



CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	22.7#	new	163	Guide			Surface Oil string
5-1/2"	14#	new	2025	Guide			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11-1/4"	8-5/8"	173	175	Halliburton 2 Plug		
7-7/8"	5-1/2"	2024	100	Halliburton 2 Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand Oil fracked open hole 2024-2170 with 40,000 gallons oil and 40,000 pounds sand, treating pressure 800 pounds. Average injection rate 67 barrels per minute.

Result of Production Stimulation 96 BOPD

Depth Cleaned Out _____