


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079082
Unit Northeast Blanco
Unit Agreement No. 1, Sec. 929



SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	SEP 26 1957
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	U. S. GEOLOGICAL SURVEY
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	FARMINGTON, NEW MEXICO
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Subsequent Report of Sandfrac.....	I

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 24, 1957

Well No. 41-25 is located 1240 ft. from N line and 1650 ft. from E line of sec. 25

14N/12E/4 Sec. 25 31N 8W 141PM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Blanco Mesaverte San Juan
(Field) (County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6384 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

On 9-12-57, perforated the Point Lookout zone thru 5-1/2" casing with 2 holes per foot 5581'-5624', 5645'-5662', 5668'-5672', 5676'-5689', 5692'-5696', 5699'-5703', 5708'-5714', 5716'-5726', 5732'-5743' & 5748'-5754'. Sand-water fraced with 59,400 gals. of water (including flush) and 50,000 lbs. of sand. Injected 80 rubber balls in 4 stages during treatment. Maximum treating pressure 2500 PSI. Minimum treating pressure 1425 PSI. Final pressure zero PSI. Average injection rate 53 barrels per minute.

Set bridge plug at 5502' and perforated the Menefee & Cliffhouse zones thru 5-1/2" casing with 2 holes per foot 5270'-5284', 5293'-5308', 5316'-5320', 5349'-5355', 5380'-5394', 5418'-5432', 5438'-5462', 5476'-5480' & 5489'-5497'. Sand-water fraced with 58,250 gals. of water (including flush) and 50,000 lbs of sand. Injected 60 rubber balls in 3 stages during treatment. Maximum treating pressure 1650 PSI. Minimum treating pressure 1300 PSI. Final pressure zero PSI. Average injection rate 54 barrels per minute.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blackwood & Nichols Company (Unit Operator)

Address P. O. Box 1237
Durango, Colorado

Original Signed
By by Delasso Loos Delasso Loos

Title Field Superintendent