UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-015
Expires: March 31, 1993

GIRTORY NORTHER AND		5. Lease Designation and Serial Number
SUNDRY NOTICES AND REPORTS ON WELLS		SF-079004
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir, Use "APPLICATION FOR PERMIT" for such proposals		6. If Indian, Allottee or Tribe Name
1. Oil Gas Other		7. If Unit or CA, Agreement Designation
 Phillips Petroleum Company 5525 Hwy. 64, NBU 3004, Farmington, NM 87401 (505) 599-3454 Location of Well (Footage, Sec., T., R., M., or Survey Description) 1160' FSL 6 1700' FWL Section 10, T-31-N, R-8-W 		San Juan 32-8 Unit 8. Well Name and No. San Juan 32-8 Unit #5
		9. API Well No. 30-045-10850
		10. Field and Pool, or Exploratory Area Blanco Mesaverde
		11. County or Parish, State
12. CHECK APPROPRIATE BOX(s) TO I	NOTO THE NAME OF A VOTE OF THE OWNER.	San Juan, New Mexico
· · · · · · · · · · · · · · · · · · ·	NDICATE NATURE OF NOTICE, REPORT, OR	OTHER DATA
TYPE OF SUBMISSION	Т	YPE OF ACTION
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off
13. Describe Proposed or Completed Operations (Cla	Completion of	Conversion to Injection Dispose Water results of multiple completion on Well or Recompletion Report and Log form.)
RIH and set CIBP ± 20' below casing coll	ar at \pm 4500'. Dump bail 5 sxs cement on th 6-1/4" bit. Air drill to 6200' TVD. RIH	ton of CIBP. Bottom of anchoratock will be
PREFLUSH: 20 bbls Mud Flush 10 bbls fresh water		
LEAD CEMENT: 50 sxs 65:35 POZ ceme	ent with 12% gel, 0.25 lb/sxs Flocele + 2% of	CaCl ₂ mixed at 12.0 ppg and 2.18 cf/sx.
TAIL CEMENT: 100 sxs Class B cement	+ 0.25 lb/sx Flocele + 2% CaCl ₂ mixed at 1	5.6 ppg and 1.18 et sx
RU electric line unit. Run GR-CCL-CBL-	VDL from PBTD to 100' above TOC. Perfor	ate the Mestvende formation.
Frac Well.		111 JUL 2 0 3894 5
Land 2-3/8", 4.7 lb/ft, J-55 tubing \pm 100	o' above the top perforation.	OIL CONE DING
Pressure test wellhead and RD and release	se rig. Put well on production.	DIST. 3
14. I hereby certify that the foregoing i	s true and correct. ely Title Environmental Enginee	r Date 7-11-94
(This space for Federal or State office us	e)	
Approved by Conditions of approval, if any:	Title	Date
Title 18 U.S.C. Section 1001, makes it a United States any false, fictitious or fr	crime for any person knowingly and willfully audulent statements or representations as to	to make any department or agency of the any matter within its tendadiction.

PHILLIPS PETROLEUM COMPANY--FARMINGTON AREA

ILLIF

-	escription: <u>1</u> San Juan	160' FSL, 1700' FWL, Section Sta	<u>10, T32N, R8W</u> te: N M
•	Vildcat Mesa		
Status:	Shut in		
Tbg.:	1855' 1-1/4" 2	.3 lb/ft Kobe Line (top)	
Other:	4130' 1" 1.8 L	b/ft 10 round EUE	
Date Dr	illed: <u>9/25/53</u>	 	
		There is no record in the w	
(or pr	oposed) on this	well since it was commleted i	n 10/53.

Open hole completion TD a 6040'