

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(*Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS		5. LEASE DESIGNATION AND SERIAL NO.	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)		14-20-0663-1112	
1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR		Nesque	
3. ADDRESS OF OPERATOR		7. UNIT AGREEMENT NAME	
B-1234, Farmington, New Mexico			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface		8. FARM OR LEASE NAME	
540' FNL 810' FEL		Shoreline	
14. PERMIT NO.		9. WELL NO.	
		1	
15. ELEVATIONS (Show whether DP, ST, GR, etc.)		10. FIELD AND POOL, OR WILDCAT	
4940 Gr.		Wildcat	
		11. SEC., T., E., M., OR ELS. AND SURVEY OR AREA	
		See 14, T31N P12W	
		12. COUNTY OR PARISH	
		San Juan	
		13. STATE	
		New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 6-16-66 Bailed hole to 1250' - encountered water flow from below 8 5/8" casing
- 6-17-66 Attempted to pump into well with Bensell-water flow increasing.
- 6-18-66 Cleaned out hole with cable tools - well flowing approx. 100 bbls. per hour of (20,000 pp cl) salt water. Set Baker cast iron bridge plug at 1260' - dumped 4 sk cement on top of B. P.
- 6-19-66 Bailed hole dry to 1450'.
- 6-20-66 Ran Garmaray correlation log - Perf. 2 holes at 1400' - bailed fresh water.
Perf. 2 holes at 1370' - bailed fresh water.
Perf. 2 holes at 1359' - bailed fresh water.
Perf. 2 holes at 1321' - bailed fresh water.
- 6-21-66 Shut down
- 6-22-66 Perf. 2 holes at 1273', 1198', 1129', 1066' and 1007' - bailed hole for six hours - no show of oil

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Dyer TITLE Engineer DATE 12-5-66

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

RECEIVED

DEC 6 1966

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.