

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-0603-8472

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shannon

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

See 14, T10N R10W

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Thomas A. Duane

3. ADDRESS OF OPERATOR
Box 234, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
540' FNL 810' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)
4960 E

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL


ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 7-11-66 Ran Baker bridge plug and full bore packer on 2 3/8" tbg. Straddled and snubbed each set of perf.
- 7-12-66 Set full bore and bridge plug across perf. at 1007', small show of oil. Ran Baker bridge plug and packer.
- 7-13-66 Plugged back hole with gravel and cement to 1065'.
- 7-14-66 Spotted five sx cement 1065' to 1055'.
- 7-15-66 Ran 2 3/8" tbg. and packer. Halliburton acidized perf. at 1007' w/250 gal. 15% HCl. Breakdown 1000 psi, Max. 1500 psi, Ave. I.R. - one bbl per min. Snubbed well - well producing est. 200 bbls. of water per day with 1% oil. The oil is dark green and 54° API gravity.



18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Duane TITLE Engineer

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

DATE _____

*See Instructions on Reverse Side

