STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

ાં ા OIL CONSERVATION DIVISION

NOV 2 4 1939 --

Page 1 Rayland 10/01/78

This form is not to be used for reporting

	This form be used for packer leak Southeast	reporting	NORTHWEST NI	EW MEXICO PA) ACKER-LE	DIIL AKAG		DIM	2 2
perator .		MOCO PRODUC	TION COMPANY FARMINGTON, N					Wel No.	1
ocation f Well: Ur	nit D	_ Sec. <u>33</u> 1	₩p. 30 N	Rge	9	W:	Coun	<u> </u>	SAN JUAN
		NAME OF RESERVO	R OR POOL	TYPE OF PR (CII or Gas			THOD OF PROD. Flow or Art. Uit)		PRGD, MEDIUM (Tbg. or Cag.)
Upper Blanco Ft Sand				GAS	S F		FLOW		TBG
Lower						FLCW			TBG
				W SHUT-IN PE	ESSURE I	DATA			
Upper Completion	our, date shi	ut-in p/ 1999	Langth of time shut 72 HOU		SI press. paig	16	1	Stabilized?	(Yes or No) YES
Lower Completion	our, date sh	6/ 1999	72 HOU		SI press. psig	6 A	SAL' 1	Stabilized?	(Yes or No)
				flow test i	NO. 1				
onimenced 41	t thour, date); #			Zone produ	ucing (Up	per or Lowert		
TIME (hour, de		LAPSED TIME SINCE*	PRESS Upper Completion	Lower Completion	PROD. Z			RE	EXRAM
1/16/	, 99	Day 1	139	162			вотн до	NES SH	HI TUI
u /17 /	99	Day 2	170	162			BOTH ZO	NES SH	HUT IN
11/18/	99	Day 3	177	162			BOTH ZO	NES S	HUT IN
11/19/	99	Day 4	116	162			FLOW U	Pper	ZONE
11/20/	99	Day 5	92	162			11	{ !	11
11/21/	99	Day 6	88	162			11		11
Production	n rate di	uring test		*TAKE N	BY JE	€€ L	nc DONA U	O	
Oil:		BOP	D based on	Bbls. i	a	Houn	i(Gray	GOR
C25:		 	MCF	PD; Tested that	ı (Orifice o	r Mese	:::):		
			MID-T	EST SHUT-IN P	RESSURE	DATA			
Upper Completion	Hour, date s	Nu(-IN	- Length of time sh	ut⊣n	SI press. psig	I		Stacilize	d? (Yes or No)
Lawer Completion	Hour, date s	niutiin	Langth of time an	ut-in	SI press. paid	3		Stantilze	d? (Yes or No)

FLOW TEST NO. 2

			Zone producing (Upper or Lowert:			
TIME (hour, date)	LAPSED TIME SINCE **	Upper Completion Lower Completion		PROD. ZONE TEMP.	REMARKS	
				i carr.	· · · · · · · · · · · · · · · · · · ·	
						
						
uction rate o	1			{		
		мст	JEN. 1 1 1 1			
arks:			D: lested thru	(Orifice or Mere	r):GOR	
uks:			D: lested thru	(Orifice or Mete	r):	
eby certify the	nat the informatio	n herein convaine	d in			
eby certify the	nat the informatio	n herein containe	d is true and cor	uplete to the be	st of my knowledge.	
eby certify th		n herein containe	d is true and cor	uplete to the be		
eby certify the oved w Mexico O	nat the informatio	n herein containe 1999 ivision	d is true and con	nplete to the be	st of my knowledge.	
reby certify d roved ew Mexico O	NOV 24	n herein containe 1999 ivision HARLIE T. PERRIN	d is true and cor	nplete to the besperator Amo	oco Production Company	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such term thall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fraccure treatment, and whenever remedial work has been done on a well during which the packet or the tubing have been disturbed. Teru shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accor-
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shur-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at bourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing . temperatures (gas zones only) and gravity and GOR (oil zones only).