

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

Contract No. 14-20-0603-742

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

None

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Rijan Oil Company, Inc.

9. WELL NO.

No. 1 Rijan

10. FIELD AND POOL, OR WILDCAT

Slickrock Pool Extension

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31T 34N-R16W

12. COUNTY OR PARISH 13. STATE

San Juan County N. Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL
WELL ☐GAS
WELL ☐

OTHER

Field Extension

2. NAME OF OPERATOR

Rijan Oil Company Inc.

3. ADDRESS OF OPERATOR

341 Korber Bldg. Albuquerque, N. Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' fsl, 170' fwl

14. PERMIT NO.

U.S.C.S. June 30, 1967

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5037' Gr. (Corrected Elevation)
5043' RT

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 30' of 7 5/8" casing and cemented to surface with 15 sacks. Set 745' of 4.5" casing and cemented to surface with 95 sacks of class "A" regular cement by Haliburton. Drilled with air to 790'. Well making some oil and sulfur water in the Dakota formation. Cemented with 30' sacks regular cement from 790' to inside of 4.5 inch casing. Cemented 10 sks. of regular at top of casing and set surface marker and cleaned up location. Top Dakota formation 785'. Air drilled from 745' to 790'.

RECEIVED

OCT 2 1967

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

18. I hereby certify that the foregoing is true and correct.

SIGNED

DIST. Geologist

DATE

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side